

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 477100

PRIMARY CORNER DESCRIPTION C C for Secs. 2 & 3 only, T28-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5440)

Intersect 6th standard parallel, 167 lks. W. fo cor. secs. 34 & 35.

Set Cedar post 3 ft. long, 4" sq., 24" in the ground for closing cor. secs. 2 & 3, marked C C T28S R2W on S.; S2 on E.; and S3 on W. face, with 2 grooves on E. and 4 grooves on W. face, from which

A Cedar 7" dia., bears S.51°E., 81 lks. dist. mkd. T28S R2W S2 BT.

A Fir 6" dia., bears S.20°W., 40 lks. dist. mkd. T28S R2W S3 BT.

Fd. and used in GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5502-03)

Survey by Romanso E. Ware and Ronald A. Quimby - For: U.S. Forest Service - May 1980 - M 79-45

Found - 3/4" Iron rod with alum. cap mkd. "USPC Prop. Cor. T27S 34 S3 S2 T28S R2W RE 4287". (Not of record)
30" Cedar stump bears N.18°E., 26.6 ft. with visible scribes.

11" Cedar stump bears S.50°E., 56.6 ft. with visible scribes, down.

New BTs- 8" Fir bears S.74°E., 9.9 ft. scribed T28S R2W S2 BT
6" Yew bears S.16°W., 23.3 ft. scribed T28S R2W S3 BT.

8" Cedar bears N.28°W., 50.5 ft. scribed T27S R2W S34 BT.

Brass washer mkd. RLS #1654 set in BT faces and set post and sign 2.7 ft. West of corner.