

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4932)

Set a Cedar post, 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S34 on W & 35 on E faces from which
A fir, 18" dia., bears S.40°10'E., 79 lks., mkd: 1/4 S35 BT.
A hemlock, 24" dia. bears S.54°40'W. 63 lks. mkd: 1/4 S34 BT
No trace of Derricks 1/4 sec. cor. can be fd after diligent search. Note - We have no record of Derrick setting this corner. JC DCSO 7/2008

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Nov. 7, 1968 - C.S. File 54/27-155

Found - 1 1/2" IP & steel pipe with US Plywood Alum cap properly mkd, unrecorded & set from OBTs as follows:
18" now 18" Fir, S.40°E., 52.1 ft., now decayed stump, scribe visible on unhealed blaze.
24" now 28" Hemlock S.54 3/4°W., 41.6 ft. alive, old scar unopened, rescribed "1/4 S34 BT" & alum. tag #4287.
New BT - 26" Hemlock, S.1°E., 36.3 ft. mkd. "1/4 S35 CS BT"
This corner lies in marshy area in clearing approx 11 ft in dia

Douglas Co. Surveyors Office - Gary Langlitz - Mike Tompkins - Sept. 13, 1976 - C.S. File 59/24-11

Found - 1 1/2" I.P. firmly set with Alum cap attached stamped USPC Property cor. T27S R2W 1/4 34 35 RE 4287. This monument is unrecorded as noted in 1968 ren.
In order to verify this unrecorded monument, we open what is indicated to be the orig. SW BT:
An Orig. 24" now 28" Hemlock stump with rescribing "1/4 S34 BT" visible on an unhealed blaze. We open this stump and find at approx. 60 years by ring count, an old face and plain scribing "S 34" bears S.54°40'W., 41.6 ft. from the cor. monument (Record S.54°40'W., 41.6 ft.)
We find no trace of the orig. SE bearing tree.
We note the following bearing object:
A bridge spike, driven in the top center of a 58" Fir stump, stamped "34" bears N.17°W., 54.4 ft.
The lookout tower on Red Butte bears S.63°E. This corner is located in a clearcut area.