TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4933)

Set a Hemlock post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S 27 on W & 26 East face from which
A Hemlock, 12" dia. bears S.26°40'E. 29 lks. mkd: ¼ S26 BT
A hemlock, 18" dia. bears N.57°10'W. 12 lks. mkd: ¼ S27 BT
Derricks ¼ sec. cor. which I now destroy, bears N.26°40'E., 4.50 chs. Note - We have no record of Derrick setting this corner. JC DCSO 7/2008

Thomas E. Shrum, Jr. - For: US Plywood Corp. - April 17, 1963 - C.S. File 51/254-17

Found - 1½" I.P. (Set in 1954)
18" Hemlock, N.57°W., 8.0 ft. (down & rotten)
Set - 2½" Alum. Cap
No trees within limits to scribe.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Nov. 1968 - C.S. File 54/27-156

Reported as not found.
Dense brush & Logging Debris