

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4936)

Set Fir post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 14, 15, 22, & 23, marked T27S S 14 on NE, R2W S 23 on SE, S 22 on SW, S 15 on NW faces, with 3 notches on S & 2 notches on E edges; from which

A fir, 26" dia. bears N.67°E. 35 lks. mkd: T27S R2W S14 BT

A cedar, 30" dia., bears S.83½°E., 34 lks., mkd: T27S R2W S23 BT.

A fir, 30" dia. bears S.45°W. 96 lks. mkd: T27S R2W S22 BT

A fir, 30" dia. bears N.65°W. 68 lks. mkd: T27S R2W S15 BT

Derricks cor. for secs. 14, 15, 22, & 23 which I now destroy bears N.14°E., 5 chs.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - April 1968 - C.S. File 54/40-76

Found - Orig. 26" fir now 28" stump, N.67°E., 23.1 ft., scribe visible.

Orig. 30" fir now 36" stump, pushed out of place, S.83½°E., 22.4', shows scar.

Orig. 30" now 34" fir, alive S.45°W., 63.4 ft. shows good scar.

Orig. 30" now 34" fir, alive N.65°W., 44.9 ft. shows good scar.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R2W
(N side of cat Rd) OFFICE S 15 | S 14
1968 S 22 | S 23

New BTs- 15" Pine N.77°E. 53.7 ft. mkd. T27S R2W S14 CS BT.

8" D.Fir S.72°E. 65.0 ft. mkd. T27S R2W S23 CS BT.

Note - This corner lies on N. side recent Cat, skid road in thinned area.

Fd. ok, R Geisler, 6/19/1986 - C.S. File 63/34