TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4888-9)

Set a basalt stone 12x8x8", 9" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 18" dia., bears N.19°W., 19 lks., mkd: ¼ S10 BT.
A fir, 18" dia., bears S.54°E., 12 lks., mkd: ¼ S11 BT.
I destroy old ¼ sec. cor. & marks on BTs
Note: We have no record of this corner being previously set
JC DCSO 8/2008

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Jan. 1965 - C.S. File 51/254-23 & Dec. 1968 M37-18

Found - D.Fir snag 30" dia., N.13½°W., 12.1 ft.
Set - 2½" dia., alum. cap
Hemlock 7" dia., N.31½°W., 27.3 ft.
W.Fir 7" dia., S.50°E., 38.6 ft.

Fd. OK VRT, DCSO 12/1968 - C.S. File 54/40