

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4877)

Set maple post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 2, 3, 10, & 11, marked T27S S 2 on NE, R2W S 11 on SE, S 10 on SW, S 3 on NW faces, with 2 notches on E & 5 notches on S edges; from which
 A fir, 20" dia. bears N.15°E., 65 lks. mkd: T27S R2W S2 BT
 A maple, 6" dia., bears S.75°E., 58 lks., mkd: T27S R2W S11 BT.
 A maple, 8" dia., bears S.45°W., 70 lks., mkd: T27S R2W S10 BT.
 A fir, 20" dia. bears N.10°W., 58 lks. mkd: T27S R2W S3 BT

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4898)

The cor. of secs. 2, 3, 10 & 11, a post 4" sq. mkd as described by the Surveyor General & as the BTs had been killed by fire & marks nearly obliterated, I reestablish this cor. by setting in place of old post a basalt stone 12x9x6", 9" in the ground mkd with 5 notches on S & 2 notches on E edge, from which
 A fir, 36" dia. bears N.19°E., 83 lks. mkd: T27S R2W S2 BT
 A fir, 20" dia. bears S.50°E. 94 lks. mkd: T27S R2W S11 BT
 A maple, 10" dia., bears S.45°W., 70 lks., mkd: T27S R2W S10 BT.
 A cedar, 15" dia., bears N.59°W., 75 lks., mkd: T27S R2W S3 BT.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group #351, surveyed July/Aug. 1957 - (DCSO records Vol. 29 Page(s) 12206)

The cor. of secs. 2, 3, 10, & 11, monumented with a basalt stone, 12x9x6", 8" above ground, firmly set, with 5 notches on the south & 2 notches on the east edge, from which the remains of the orig. BTs as follows:
 A fir stump, 36" dia., bears N.19°E., 83 lks., with healed blaze.
 A dead fir, 32" dia., bears S.50°E., 94 lks., with B & other illegible scribe marks visible on opened blaze.
 A cedar, 24" dia., bears N.59°W., 75 lks., with T27 R2W S3 BT visible on opened blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked: continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3, 10, & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T27S R2W
S 3 | S 2
S 10 | S 11
1957

from which

A fir, 6" dia., bears N.60°E., 87 lks. mkd: T27S R2W S2 BT

A cedar, 5" dia. bears S.28½°E. 30 lks mkd: T27S R2W S11 BT

A sugar pine, 5" dia., bears S.27°W., 28 lks., mkd: T27S
R2W S10 BT.

A fir, 8" dia. bears N.57½°W., 33 lks. mkd: T27S R2W S3 BT

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone - Sept. 1962 - C.S. File 49/28-8

Found - GLO brass cap at corner.

6" Fir N.60°E., 57.4 ft. alive & standing, scribing still visible.

5" cedar S.28½°E., 19.8 ft. alive & standing, scribing still visible.

8" fir N.57½°W., 21.8 ft. alive & standing, scribing still visible.

24" cedar N.59°W., 49.5 ft. alive & standing, scribing still visible (Orig. BT)

5" Pine S.27°W., 18.5 ft. standing but dead, scribing visible.

New BT - 9" Hemlock S.22°W., 29.7 ft. mkd: T27S R2W S10 CS BT

Fd. & used on BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #351 surveyed April/May 1978 - (DCSO records Vol. 41 Page(s) 16172)

Fd. Ok by Geisler, 4/1984 - M90-55

Glen Baughman - For: USFS - Nov. 1989 - C.S. File 63/85-42

Found - 2½"x30" galv. IP with a 3" dia., brass cap stamped "T27S R2W" 3 2 10 11, firmly attached to the top. The monument had been ran over by a cat during recent logging operation & was lying on its side in relatively good position to the BT.

13" hemlock bears S.22°W., 29.7 ft. (1962)

24" cedar bears N.59°W., 49.2 ft. (1905 rec 49.5 ft)

41" fir stump bears N.19°E. 56.0 ft (1905 rec 54.8 ft)

30" fir stump bears S.47°E., 62.9 ft (1905 rec 62.0')

15" hemlock (rec. fir) bears N.57°30'W., 22.3 ft. (1957 rec. 21.8 ft. to face)

13" fir bears N.60°E., 57.6 ft. (1957 rec. 57.4 ft.)

continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set - 15" cedar bears S.25°E. 19.8 ft (1957 rec S.28°30'E.)
I reset the monument 24" in the ground & built a 36" dia., stone mound to the top of the pipe.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500, Surveyed Aug./Nov. 2011 - (DCS0 records BLM Plat T27-2W 2012-1 & Vol. 58 Pages 22947-8)

The cor. of secs. 2, 3, 10, & 11, perpetuated by Baughman in 1989, monumented with an iron post, 2½" dia., firmly set, projecting 2" above the top of a mound of stone, 3 ft. base, 1 ft. high, with brass cap (properly) mkd.

from which the remains of BTs mkd by Roberts
A sawed, decayed fir stump, 39" dia., bears N.19°E., 54.8 ft. with scribe marks 2W B visible on an open blaze.
A decayed fir stump, size indeterminate, bears S.50°E., 62.0 ft. with fragmentary scribe marks visible on an open blaze.
A cedar, 30" dia., bears N.59°W., 49.5 ft. with a healed blaze.

and the remains of a BT mkd by Corbin
A fir, 24" dia., bears N.60°E., 57.4 ft. with a healed blaze.

A decayed cedar snag, size indeterminate, bears S.28½°E., 19.8 ft. with no marks visible.

A hemlock stump, size indeterminate, bears N.57½°W., 21.8 ft. with no marks visible.

and the remains of a BT mkd. by Godfrey in 1962, misidentified as mkd. by Byron in 1960 by Jelly

A decayed hemlock stump, size indeterminate bears S.21½°W., 29.7 ft. with scribe marks R2W S10 CS visible on an open blaze, lying downhill of which is the fallen, sawed decayed, hemlock trunk, size indeterminate, with no marks visible. (Rec. N.21½°W.)

and new BTs

A fir, 12" dia., bears S.51½°E., 38.4 ft., mkd: T27S R2W S11 BT.

A fir, 5" dia., bears S.17¼°W., 47.1 ft., mkd: T27S R2E S10 BT.

Fd. BC & BTs 6/2015 - by K Hoffine - M169-57