

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4878)

-----  
Set Laurel post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S on E & W faces; from which  
A sugar pine, 9" dia., bears S.10°E., 21 lks., mkd: 1/4 S BT  
A maple, 6" dia., bears N.86°W., 32 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group #351, surveyed July/Aug. 1957 - (DCSO records Vol. 29 Page(s) 12207)

-----  
Point for the 1/4 sec. cor. of secs. 2 & 3, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 1/2" dia., 26" in the ground with brass cap marked:

T27S R2W  
1/4  
S 3 | S 2  
1957

from which  
A cedar, 8" dia., bears S.86°E., 55 lks., mkd: 1/4 S2 BT.  
A cedar, 8" dia., bears S.34°E., 87 lks., mkd: 1/4 S2 BT.  
No tree available in sec. 3.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Dec. 1968 - C.S. File 54/40-142

-----  
Found - 1957 cadastral brass cap, in place.  
8" now 10" cedar N.86°E., 36.3 ft. scribed "1/4 S2 BT Dan Boone" healing.  
8" now 10" cedar S.34°E., 57.4 ft. scribed "1/4 S2 BT NN" healing.  
New BT - 9" D.Fir S.71°W., 5.3 ft. mkd: "1/4 S3 CS BT"  
This corner lies about 280 ft. N of Little River Road on moderate S slope.

Fd. & used on BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #983, surveyed May/Aug 1979 - (DCSO records Vol. 44 Page(s) 16922-3)

Fd. Ok 4/1984 by Geisler, M90-55