

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by S.C. Flint, Contract #459, dated August 3, 1882  
- (DCSO records Vol. 10 Page(s) 4184)

-----  
Set Laurel post 4 ft. long, 4" sq., 24" in the ground for  
cor. to secs. 2, 3, 34 and 35 marked T26S S35 on NE.; R2W S2  
on SE.; T27S S3 on SW.; S34 on NW. faces with 2 notches on  
the E. and 4 on the W. edges, from which  
A Fir 20" dia., bears N.55°E., 76 lks. dist. mkd. T26S R2W  
S35 BT.  
A Fir 14" dia., bears S.20°E., 100 lks. dist. mkd. T27S  
R2W S2 BT.  
A Fir 30" dia., bears S.75°W., 57 lks. dist. mkd. T27S R2W  
S3 BT.  
A Fir 24" dia., bears N.68°W., 55 lks. dist. mkd. T26S R2W  
S34 BT.

GL0 survey by William N. Gibb, Deputy Surveyor, under  
Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 10  
Page(s) 4224)

-----  
At cor. secs. 34, 35, 2 and 3, which is a stake greatly  
decayed, marked and witnessed as described by the surveyor  
general. Set granite stone 8x10x14 ins., 10" in the ground  
for cor. secs. 34, 35, 2 and 3, marked with 4 notches on W.  
and 2 notches on E. edge.

GL0 survey by C.M. Collier, Deputy Surveyor, under  
Instructions dated May/Sept. 1913 - (DCSO records Vol. 10  
Page(s) 4262-63)

-----  
The Sec. cor. which is a post, nearly decayed, witnessed by  
the two westerly bearing trees and stumps of the other trees  
described by the surveyor general. I destroy this cor. and  
re-establish it in the same place, as follows:  
Set a basalt stone 13x8x8 ins., 8" in the ground, for cor.,  
marked with 2 notches on E. and 4 notches on W. edge; from  
which  
A Laurel 7" dia., bears N.57°E., 71 lks. dist. mkd. T26S  
R2W S35 BT.  
A Laurel 7" dia., bears S.82°E., 84 lks. dist. mkd. T27S  
R2W S2 BT.  
A Fir 32" dia., bears S.75°W., 57 lks. dist. mkd. T27S R2W  
S3 BT. (orig. BT)  
A Fir 30" dia., bears N.68°W., 55 lks. dist. mkd. T26S R2W  
S34 BT. (orig. BT)

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3; 34 & 35, T26-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Fd. and used in GLO Survey by Fred Mensch, U.S. Surveyor Under Special Instructions dated May 25, 1916 - (DCSO records Vol. 10 Page(s) 4289-90)

BLM Resurvey by Harold D. Corbin, Cadastral Surveyor, under Special Instructions dated June 21, 1957 - (DCSO records Vol. 29 Page(s) 12204)

-----  
The Sec. cor., monumented with a basalt stone 13x8x8 ins., 8" above ground, firmly set, mkd. with 2 grooves on the E. and 4 grooves on the W. face, from which the remains of the original bearing trees, as follows:

- A madrone 7" dia., bears N.57°E., 71 lks. dist. with scribe marks BT visible on opened blaze.
- A Madrone 9" dia., bears S.82°E., 84 lks. dist. with healed blaze facing the cor.
- A Fir stump 36" dia., bears S.75°W., 57 lks. dist. with healed blaze facing cor.
- A Fir 36" dia., bears N.68°W., 55 lks. dist. with healed blaze facing the cor.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

T26S R2W	
S 34	S 35
S 3	S 2
T27S	
1957	

from which

- A Fir 13" dia., bears N.25½°E., 39 lks. dist. mkd. T26S R2W S35 BT.
- A Fir 13" dia., bears S.43°E., 75 lks. dist. mkd. T27S R2W S2 BT.
- A Fir 13" dia., bears S.29¼°W., 87 lks. dist. mkd. T27S R2W S3 BT.
- A White Fir 10" dia., bears N.76°W., 112 lks. dist. mkd. T26S R2W S34 BT.

Deposit original cor. stone alongside iron post.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew July 1967 - C.S. File 54/40-26

-----  
Found - 1957 Cad. brass cap and original corner stone.  
13" now 15" Fir N.25½°E., 25.7 ft., alive, healed blaze.  
13" now 13" Fir, down, S.43°E., 49.5 ft., scribe visible on unhealed blaze.

(Cont. Next Page)

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3; 34 & 35, T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

13" now 16" Fir S.29¼°W., 57.4 ft., alive, healed blaze.  
10" now 14" D.Fir (not W.Fir) N.76°W., 73.9 ft., alive, healed blaze.  
29" now 15" Laurel S.82°E., 55.4 ft. alive, healed blaze.  
Do not open healed blazes. Only orig. SE. BT standing.  
New BT - 15" D.Fir S.75°E., 20.2 ft. mkd. T27S R2W S2 CS BT.  
Corner lies on top of spur, ridge sloping South at old cutting corner. Secs. 35, 2 and 3 cut off.

Fd. OK, April 1984 by R. Geisler - M 90-55

Bruce Shaner - 11/2000 - C. S. File 65/36-2K & M132-70  
-----  
Found - ¾" brass cap w/2½" IP, properly mkd.  
30" D.Fir, face o/grown, bears N.25½°E., 25.7 ft.  
24" D.Fir, face o/grown, bears S.29¼°W., 57.4 ft.  
24" D.Fir, face o/grown, bears N.76°W., 73.9 ft.  
22" Madrone, face o/grown, bears S.82°E., 55.4 ft.  
28" D.Fir, face o/grown, (rec. 15") bears S.75°E., 20.2 ft.  
New - 6 ft. alum. post, bears West, 1.0 ft.  
6 ft. alum. post, bears North, 1.0 ft.  
Note - Corner lies on top of major ridge, runs NW-SE.  
Compass declination 20°E

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 11/29/2021 (Filed 4/7/2022) - C.S. File 67/51-35  
-----  
Found - ¾" brass cap (properly mkd) on 2½" Iron Pipe projecting 5" orig. stone now crumbled on South edge.  
24"x3½' sawn burnt Fir stump S.73°W., 37.6 ft. (rec S.75°W., scribes burnt off. 1882  
36"x25 tip out & burnt Fir N.68°W., 36.3 ft. fully healed blaze. 1882  
31"x1½' sawn fir stump N.25½°E., 25.7 ft. 1957  
28" D.Fir S.27°W., 56.5 ft. (Rec. S.29¼°W., 57.4 ft.) 4" mag. 1957  
25" D.Fir N.77½°W., 73.9 ft. (rec. N.76°W.) 4" mag nail right side center. 1957  
23"x1½' sawn broken Madrone stump S.85°E., 55.4 ft (rec S.82°E.) 1913  
32"x1½' burnt-sawn Fir stump S.75°E., 20.2 ft. to 4" mag nail top center. 1967  
Alum post N-E-W  
Continued next pg

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T26-2

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Note - See sketch in file  
Area burnt 9/2020  
Compass decl. 14½°E.  
Lat: 43°15'26.46" N 122°54'42.78" W