

PRIMARY CORNER DESCRIPTION A P on So. Bdy. Sec. 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 12 Page(s) 4866-67)

Set Yew post 3 ft. long, 3" sq., 24" in the ground for
standard ¼ sec. cor. marked on N. face S C ¼ S., from which
A Fir 30" dia., bears N.50°W., 19 lks. dist. mkd. S C ¼ S
BT.
A Fir 32" dia., bears South 9 lks. dist., mkd. S C ¼ S BT.

GLO Resurvey by Morris Wygant, Compassman for Zachariah
Derrick, U.S. Deputy Surveyor, Under Contract #779, dated
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4903)

The old standard ¼ sec. cor. which is a post, firmly set,
mkd. and witnessed as described by the surveyor general,
bears N. 41 lks. dist. As this line is badly out of limits
and these old standard cors. will no longer refer to the
secs. on the North and do not refer to the secs. on the
South, I now change this cor. to an angle point, as follows:
Destroy all marks on cor. and mark A P on N. face, then cut
all bearing trees and remark, A P BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under
special Instructions, dated June 7, 1922 - (DCSO records Vol.
12 Page(s) 4964)

The Angle point, which is a sound Yew post, 4" sq., 12" above
ground, mkd. ¼ S35 on N. face. The BTs are as described in
the notes of the Flint survey, but as the tree N. of line is
now decayed and not suitable for permanent witness, I destroy
the marks on both the old trees; from the post
A Hemlock 24" dia., bears N.67°E., 21 lks. dist. mkd. AP
BT, New BT.
A Yew 7" dia., bears N.17°W., 16 lks. dist. mkd. AP BT,
new BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Oct. 1968 - C.S. File 54/40-93

Found - Orig. 24" now 28" Hemlock, alive, N.67°E., 13.9 ft.,
scribe visible, on unhealed blaze. Rescribe "AP
CS BT"
Orig. 7" now 9" Yew, dead and broken off 4 ft. above
ground, N.17°W., 10.6 ft., scribe visible.
Set Brass cap at cor. mkd: County Surveyors Office

T 27 S R2W A P
T 28 S

(Cont. Next Page)

1968

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 539100

PRIMARY CORNER DESCRIPTION A P on So. bdy. Sec. 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BT - 50" D.Fir N.1°W., 13.2 ft. mkd. "AP CS BT"
Corner lies on steep East slope, approx. 310 ft. East of N.
¼ cor. Sec. 2, T28-2.

Fd. OK, June 28, 1972 by V.Tracy, DCSO

Survey by Gerald V. Nygren - oct. 1988 - C.S. File 63/69-36

Found - A Brass cap on Iron pipe.
6 ft. high, 32" Hemlock stump, bears N.67°E., 13.9
ft. visible scribing.
9" Yew, dead and broken off 4 ft. above ground bears
N.17°W., 10.6 ft., visible scribing.
54" D.Fir, 4 ft. high stump, bears N.1°W., 13.2 ft.,
visible scribing.
New BTs- 8" Hemlock S.20°W., 11.0 ft. scribed "AP BT"
18" double Yew, S.70°W., 39.1 ft., scribed "AP BT"
Set 1/2" brass washers in BT faces mkd. "LS 1035"
Point lies approx. 300 ft. East of ¼ cor. for sec. 2, T28-2