

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4926)

37.00 chs.
Derricks ¼ cor. which I now destroy bears N. 3.00 chs.
40.00 chs.
Set a Fir post 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S 26 on N & 35 on S face from which
 A fir, 20" dia., bears N.11°45'E., 31 lks., mkd: ¼ S26 BT.
 A fir, 20" dia., bears S.86°10'E., 35 lks., mkd: ¼ S35 BT.
Note - We have no record of Derrick setting this corner.
 JC DCSO 7/2008

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Nov. 1962 - C.S. File 51/254-9

Found - ¾" I.R.. This rod was set by me in 1956 from the Orig. BTs subsequent logging destroyed all Orig. BTs. I now set a 2½" alum. cap in place of the iron rod & reference 2 new BTs:
Set - 2½" Alum. cap
 15" Yew, S.45°W., 5.8 ft. mkd: ¼ S35 BT
 13" Yew, N.75½°E., 47.4 ft. mkd: ¼ S26 BT.

FD. Ok by VRT, DCSO - 10/15/1968 C.S. File 54/40-81