

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4934-5)

West on true line bet. Secs. 23 & 26
At 36.00 chains:
Derricks ¼ sec. cor., which I now destroy bears N.45°E., 6.00 chs.
At 39.92½ chains:
Set a hemlock post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. mkd ¼ S23 on N & 26 on South face; from which
 A hemlock, 36" dia. bears S.88°E., 25 lks. mkd: ¼ S26 BT
 A hemlock, 20" dia., bears N.61°W., 22 lks., mkd: ¼ S23 BT

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Nov. 1962 - C.S. File 51/254-6

Found - 38" Hemlock stump, S.88°E., 16.5 ft.
 24" Hemlock stump, N.61°W., 14.5 ft.
 Scribing clear & legible. No other trees suitable for scribing within limits.
Set - 2½" alum. cap

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Nov. 1968 - C.S. File 54/40-30

Found - 1½" IP & alum. cap. 1962
 Orig. 36" now 38" Hemlock stump, S.88°E., 16.5 ft., scribe visible on open blaze.
 Orig. 20" now 24" Hemlock stump N.61°W., 14.5 ft., scribe visible on open blaze.
New BTs- 6" D.Fir S.12°W., 5.6 ft., mkd: "¼ S26 CS BT"
 6" D.Fir N.41°E., 26.2 ft., mkd: "¼ S23 CS BT"
This corner lies on top of spur sloping north in D.Fir reproduction.

Fd. Ok 6/1980, RLS 1654 - M79-44