

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4876-7)</p> <p>-----</p> <p>Set cedar 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N & S faces; from which A maple, 6" dia., bears N.5°E., 13 lks., mkd: ¼ S BT. A fir, 36" dia., bears N.10°E., 13 lks., mkd: ¼ S BT.</p>
<p>GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4897)</p> <p>-----</p> <p>The ¼ sec. cor. which is a post 3" sq., 2 ft. above the ground firmly set, marked & witnessed as described by the Surveyor General.</p>
<p>Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Ray Tracy - Mike Stone - Sept. 1962 - C.S. File 49/28-9</p> <p>-----</p> <p>Found - Fir, now 42" N.10°E., 8.6 ft., bark scribing visible "¼S", no "BT" fd but bark had been flattened with an axe, bark charred on lower face. Stump hole with clump of Maple shoots around it S.5°E., not N.5°E., 8.6 ft.</p> <p>Set - Brass cap at cor. mkd COUNTY SURVEYORS T27S R2W ¼ S <u>2</u> OFFICE 1962 S <u>11</u></p> <p>New - 7" Hemlock N.62°W., 22.0 ft. mkd: ¼ S2 CS BT. 10" Hemlock S.15°E., 18.5 ft. mkd: ¼ S11 CS BT.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Nov. 1968 - C.S. File 54/40-129</p> <p>-----</p> <p>Fd. Ok, see 1962 ren. This cor. lies 30 ft. W. of NW cor. of clear cut unit.</p>
<p>Fd. Ok 4/1984 - by Geisler, M90-55</p>
<p> </p>