

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 541500

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 11 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4887)

-----  
Set a basalt stone 14x7x6", 9" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
A W.Fir, 22" dia., bears S.23°E., 26 lks., mkd: ¼ S14 BT.  
A W.Fir, 18" dia., bears N.30°E., 56 lks., mkd: ¼ S11 BT.

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4914)

-----  
The ¼ sec. cor. bet. secs. 11 & 14 which is a stone, firmly set, marked & witnessed as described by the surveyor general, & which I now change to refer to sec. 11.

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Feb. 1964 - M29-26

-----  
Set - 2½" dia., alum. cap  
Yew 8" dia., N.01½°W., 28.5'

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Nov. 12 1968 - C.S. File 54/40-113

-----  
Found - Orig. 22" W.Fir now 36" sawed stump, S.23°E., 17.2 ft., open & find "¼ S14 BT" scribe & reverse.  
Old NE BT. down, shows scar.  
No trace of cor. stone due to fire trail at corner point

Set - Brass Cap mkd: COUNTY SURVEYORS T27S R2W  
OFFICE, 1968 ¼ S 11

New BTs- 10" Cedar S.44°E., 51.0 ft. mkd: "¼ S11 CS BT"  
10" Cedar S.50°W., 53.2 ft. mkd: "¼ S11 CS BT"

The S¼ Sec. 11 recorded in 1964 bears N.19°E., 27.1 ft.  
Dec. 23, 1968

Note - On subsequent visit to this corner, we find US Plywood (1964) alum cap removed & logging activity beginning.

Mark more BTs -  
40" D.Fir stump N.84°E., 37.1 ft. mkd: "¼ S11 CS BT"  
48" D.Fir stump N.75°W., 43.3 ft. mkd: "¼ S11 CS BT"

US Plywood's BT recorded in 1964  
10" Yew N.9°E., 54.2 ft. scribe visible & Alum tag.  
#4287  
Cedar BTs mkd by us in Sec 14 (Both OK at this time)