

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4917)

Set hemlock post, 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S 35 on W & 36 on E face; from which
A fir, 20" dia., bears N.27°10'E., 69 lks., mkd: 1/4 S36 BT.
A yew, 12" dia., bears N.85°W., 18 lks., mkd: 1/4 S35 BT.
No trace of Derricks 1/4 cor can be found.
Note - We have no record of Derrick setting this corner.
JC DCSO

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - Oct/Nov. 1968 - C.S. File 54/40-79

Found - Orig. 12" now 17" Yew, alive, N.85°W., 11.9 ft. scribe visible on nearly healed blaze, good condition.
Orig. 20" now 20" Fir N.27°E., 45.5 ft. now down, sawed stump, scar visible on underside of decayed log.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R2W OFFICE 1968 1/4 S 35|S 36
10" Hemlock, S.63 1/2°E., 13.3 ft. mkd: "1/4 S36 CS BT"
Note - Corner lies 75' S of SW cor. of clear cut unit in sec. 36.

Romanso E. Ware & Ronald Quimby - For: US Forest Service - May 1980 - M79-46

Found - 1 1/2" Iron pipe with brass cap properly mkd.
14" Hemlock bears S.63°E., 13.3 ft. with visible scribes.
18" Yew, dead and down, bears S.85°W., 11.9 ft. with visible scribes.
3" x 3" wood post 1.0 ft. East of corner.
New BT - 20" Yew bears S.70°W., 155.0 ft. scribed "1/4 S35 BT".
Brass washer mkd. RLS #1005 set in BT face.