

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor Secs 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4917-8)

Set a hemlock post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 25, 26, 35, & 36, marked T27S S 25 on NE, R2W S 36 on SE, S 35 on SW, S 26 on NW faces, with 1 notches on S & E edges; from which

- A hemlock, 18" dia., bears N.43°20'E., 19 lks., mkd: T27S R2W S25 BT.
- A yew, 18" dia., bears S.65°10'E., 39 lks., mkd: T27S R2W S36 BT.
- A fir, 24" dia., bears S.48°40'W., 9 lks., mkd: T27S R2W S35 BT.
- A fir, 30" dia., bears N.55°40'W., 30lks., mkd: T27S R2W S 26 BT.

Derricks cor. for these secs., which I now destroy bears N.55°E., 4.40 chs.

Note - We have no record of Derrick setting this corner.
JC DCSO 7/2008

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Dec. 1962 - C.S. File 51/254-11

Found - 26" D.Fir stump S.49°W., 5.6 ft. scribe good condition (Orig. 24" D.Fir)
36" D.Fir stump N.55°W., 20.0 ft. rescribe: S26 BT (Orig. 30" D.Fir)

Set - 18" Yew, S.65½°E., 26.7 ft. Rescribe: S36 BT.
2½" Alum. cap
22" D.Fir stump, N.15½°E., 12.1 ft. mkd: S25 BT. (Orig. Hemlock for S25 is gone.)

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - Oct/Nov. 1968 - C.S. File 54/40-80

Found - U.S. Plywood Alum. cap, properly mkd.
Orig. 26" Fir stump S.49°W., 5.6 ft. good orig. scribe visible.
Orig. 36" Fir stump N.55°W., 20.0 ft. rescribed: "S26 BT"
Orig. 18" Yew, S.65½°E., 26.7 ft. alive, rescribed "S36 BT"
22" Fir stump N.15½°E., 12.1 ft. mkd: "S25 BT" (Shrum's new BT)

New BT - 15" Hemlock S.62°W. 32.7 ft. mkd: T27S R2W S35 CS BT

continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Set - 6' Steel fence post alongside alumn. scribe. No live trees N. of corner. This corner lies NE slope. Clear cut in sections 25, 26, & 35.</p>
<p>Romanso E. Ware & Ronald Quimby - For: US Forest Service - May 1980 - M79-46</p> <p>-----</p> <p>Found - 1½" iron pipe with brass cap properly mkd. 27" Fir stump bears S.44°W., 6.4 ft. with visible scribes. 24" Fir stump bears N.18°E., 11.6 ft. with visible scribes. 18" Yew bears S.65½°E., 26.7 ft with visible scribes 36" Fir stump bears N.60°W., 20.5 ft. with visible scribes.</p> <p>New BTs- 8" Fir bears N.88°W. 52.2 ft scribed "T27S R2W S26 BT" 14" Hemlock bears N.4°W., 39.6 ft. scribed "T27S R2W S26 BT"</p> <p>Brass washers mkd: RLS #1654 set in BT faces.</p>
<p>Gerald V. Nygren, LS 1035 - Oct. 1988 - C.S. File 63/69-33</p> <p>-----</p> <p>Found - 1" iron pipe with 2½" alum. cap extended 6" above ground per 1980 ren. 27" fir stump bears S.44°W., 6.4 ft. - visible scribing. 24" fir stump, bears N.18°E., 11.6 ft. - visible scribing. 18" yewwood bears S.65½°E., 26.7 ft. visible scribing. 36" fir stump bears N.60°W., 20.5 ft. visible scribing. A metal post 1 ft. north of corner. 8" fir bears N.88°W., 52.2 ft. - healed blazed. 14" hemlock snag bears S.4°E. 39.6 ft vis. scribing (Rec. per 1980 ren, map No. M79-46 is N.4°W.)</p> <p>New BT - 12" D.Fir bears S.34°W., 32.3 ft. scribed "T27S R2W S35 BT" and set 1/2" brass washer in BT face marked "LS 1035"</p>