

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4920)

-----  
Set a Hemlock post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 23, 24, 25, & 26, marked T27S S 24 on NE, R2W S 25 on SE, S 26 on SW, S 23 on NW faces, with 2 notches on S & 1 notch on E edges; from which

A fir, 48" dia., bears N.70°15'E., 27 lks., mkd: T27S R2W S24 BT.

A hemlock, 20" dia., bears S.27°E., 35 lks., mkd: T27S R2W S25 BT.

A hemlock, 24" dia., bears S.12°10'W., 65 lks., mkd: T27S R2W S26 BT.

A fir, 30" dia., bears N.11°45'W., 24 lks., mkd: T27S R2W S23 BT.

Derricks cor. of secs. 23, 24, 25, & 26, which I now destroy, bears N.45°30'E., 570 lks. Note -We have no record of Derrick setting this corner. JC DCSO 7/2008

Douglas Co. Surveyors Office - Vernon "Ray" Tracy- Oct/Nov. 1968 - C.S. File 54/40-129

-----  
Reported as not found.  
Logged & burned several years ago.  
F.AP. (Forest appraisal?) info. does not jibe with orig. field notes.