

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GL0 resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4922)</p> <p>-----</p> <p>Set a Hemlock post, 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S23 on W & 24 on E face; from which A hemlock, 10" dia., bears S.85°E., 32 lks., mkd: 1/4 S24 BT A Yew, 8" dia., bears N.80°W., 23 lks., mkd: 1/4 S23 BT. N.0°01'W., 3.75 chs. Derricks 1/4 sec. cor. which I now destroy bears East 2.50 chs. Note - We have no record of Derrick setting this corner. JC DCSO 7/2008</p>
<p>Thomas E. Shrum, Jr. - For: US Plywood Corp. - Nov. 1962 - C.S. File 51/254-6</p> <p>-----</p> <p>Found - 18" Hemlock S.85°E., 20.4 ft. 10" Yew, N.80°W., 15.2 ft. Set - 2 1/2" Alum. Cap.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perry - Oct/Nov. 1968 - C.S. File 54/40-128</p> <p>-----</p> <p>Found - No trace of 2 1/2" alum. cap as called for in 1962 renewal, probably removed during recent logging. Orig. 10" now 18" hemlock stump, S.85°E., 21.1 ft., scribe visible on opened blaze. Orig. 8" now 10" Yew, N.80°W., 15.2 ft. down under logging debris, scribe visible. Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R2W OFFICE 1968 1/4 S 23 S 24 New BTs- 5" hemlock, S.21°E., 20.7 ft. mkd: "1/4 S24 CS BT" 10" Yew N.75°W., 154.6 ft. mkd: "1/4 S23 CS BT" This corner lies 135 ft. N of creek 6 ft. wide, course NE.</p>
<p>Ronald A. Quimby, LS 1654 & Romanso E. Ware, LS 1005 - For: US Forest Service - May 1980 - M79-44</p> <p>-----</p> <p>Found - County Surveyors Office Brass Cap properly mkd. 1968 6" Hemlock bears S.21°E., 20.7 ft. with visible scribes (down). 10" Yew bears N.75°W., 154.6 ft. with visible scribes (down). 18" Hemlock stump bears S.85°E., 21.1 ft. with visible scribe. New BTs - 8" Fir bears S.26°W., 52.3 ft. scribed "1/4 S23 BT". 14" Madrona bears N.60°W. 225.0 ft scribed "1/4 S23 BT" Brass washers mkd RLS #1654 set in BT faces. Fd post 1.0' S.</p>