

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor Secs 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4922-3)

Set a hemlock post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 13, 14, 23, & 24, marked T27S S 13 on NE, R2W S 24 on SE, S 23 on SW, S 14 on NW faces, with 3 notches on S & 1 notches on E edge; from which

- A cedar, 14" dia., bears N.88½°E., 27 lks., mkd: T27S R2W S13 BT.
- A hemlock, 10" dia., bears S.62°E., 14 lks., mkd: T27S R2W S24 BT.
- A hemlock, 10" dia., bears S.37°W., 7 lks., mkd: T27S R2W S23 BT.
- A cedar, 18" dia., bears N.32°W., 67 lks., mkd: T27S R2W S14 BT.

Derricks cor. for secs. 13, 14, 23, & 24 which I now destroy bears N.45°E., 425 lks. Note -We have no record of Derrick setting this corner. JC DCSO 7/2008

Douglas Co. Surveyors Office - James W. Byron, Deputy - M. Godfrey - S Bilow - T Shrum - Nov 7, 1957 - C.S. File 49/28-1

Found - Orig. 10" now 12" Hemlock S.37°W., 4.6 ft. Tree dead & leaning. I open & find good scribing "S 23"
Orig. 18" now 24" Cedar now stump. Shows old face, rotted, no scribing found.
The original SE & NE BTs not found.

Set Brass cap at cor mkd S 14 | S 13 T27S R2W COUNTY SURVEYORS
S 23 | S 24 OFFICE 1957

New BTs- 20" Cedar bears N.32½°E., 98.4 ft. scribed T27S R2W S13 CS BT. BT at bottom small stream scribed 6' above gr.
Chiseled 4 inch "+" & "B0" on 6'x6' rock at north edge of stream bears N.28°W., 52.2'.
Chiseled 4 inch "+" & "B0" on 6'x3' rock (North side) bears S.41°E., 77.2'

Note - This area has been burned - no trees available except in NE.

Fd. Ok by VR Tracy, 11/1968 - C.S. File 54/40-121

Romanso E. Ware - For: US Forest Service - May 1977 - M65-20

Found - 1957 County Surveyors Office brass cap properly stamped. 1957
28" Cedar bears N.32°E. 98.4 ft. scribing visible.
12" Hemlock down. continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor Secs 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- A 6" D.Fir bears S.63°W., 18.0 ft. scribed T27S R2W S23 BT.
A 8" Alder bears N.32°W., 45.8 ft. scribed T27S R2W S14 BT.
A 6" D.Fir bears S.53°E., 21.6 ft. scribed T27S R2W S24 BT.

Fd. Ok by R. Quimby, 6/1980 - M79-44

John Ransom, USFS - Jonathan Drew - 11/2010 - CS File 65/72-19

Found - 2½" Brass Cap on 1" Iron Pipe, Projecting 14" above mound of rock Cap marked: "County Surveyors Office T27S S14 S13 S23 S24 R2W 1957"
19" Fir S.63°W., 18.0 ft healed double blaze
21" Fir S.53°E., 21.6 ft healed double blaze
10" Alder N.32°W., 45.8 ft dead 20 ft tall snag.
39" Cedar N.32°E., 98.4 ft visible scribe on open face "T27S R2W S13" visible
At time of visitation did not have record of two chiseled "+" "B0" on rocks in stream set in 1957 by County, did not search for.

New - Painted 6" Band around BTs and painted face blazes, new nails on signs, cleared brush around corner
Marked new tree:
6" Cedar bears N.89°30'W., 8.38 ft scribed "X" "BT" on double blaze new trees measured with tape and staff compass (15°45' dec)

Note - Take Forest road 2701 to the 120 spur, follow 2701-120 north to 110 spur, Follow 110 spur to 020 spur, follow 020 spur south-east to overgrown 170 spur walk 170 spur North to posted/blazed line. Follow line West to corner. Corner falls on West slope near creek.

Remarks- Found Steel Post approx. 2.5 FT East
Found Carsonite Post approx 4 FT. North
Line maintained East .25 Miles
PLANE COORDINATE POSITION DATA
State OR Zone UTM-10M
North 4784415
East 508750
Estab. By GCDB