

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4925)

N.0°01'W at 40.00 chs.
Set a Hemlock post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S14 on W & 13 on E face; from which
 A cedar, 10" dia., bears N.22°20'E., 29 lks. mkd: ¼ S13 BT
 A cedar, 10" dia., bears N.70°45'W., 24 lks. mkd: ¼ S14 BT
at 44.25 chs.
Derricks ¼ sec. cor. which I now destroy, bears East 2.00 chs
Note - We have no record of Derrick setting this corner.
 JC DCSO 7/2008

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Nov. 1962 - C.S. File 51/254-8

Found - 14" Cedar N.22½°E., 19.3 ft.
 18" Cedar stump N.72°W., 15.4 ft.
Set - 2½" Alum cap.

Romanso E. Ware - For: US Forest Service - May 1977 - M65-20

Found - 2½" Alum. cap on ¾" I.Rod. 1962 - stamped U.S. Plywood Property Cor. T27S R2W 13 14 R.E. 4287.
 14" Cedar bears N.22°E., 18.5 ft. visible scribing
 14" Cedar stob bears N.65°W. 15.4 ft visible scribing
New BTs- 18" Cedar bears N.10°W., 28.0 ft. scribed ¼ S14 BT.
 Rescribed 14" Cedar bears N.22°E. , 18.5 ft. scribed ¼ S13 BT.