

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Closing Cor Secs 11, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4886)

Set a basalt stone 12x6x5", 9" in the ground for cor. of secs. 11, 12, 13, & 14 mkd with 4 notches on S & 1 notch on E edge, from which

- A W.Fir, 8" dia., bears N.28°E., 71 lks., mkd: T27S R2W S12 BT.
- A hemlock, 6" dia., bears S.75°E., 55 lks., mkd: T27S R2W S13 BT.
- A hemlock, 24" dia., bears S.35°W., 37 lks., mkd: T27S R2W S14 BT.
- A W.Fir, 7" dia. bears N.23°W. 41 lks mkd: T27S R2W S11 BT

GL0 resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4913 & 4925)

Pg. 4913 - the cor. of secs. 11, 12, 13, & 14 which is a stone, firmly set, marked & witnessed as described by the Surveyor General and which I now change to refer to secs. 11 & 12 only.

Pg 4925 - Intersect South boundary of sec. 11, 109 lks., N.89°34'W., of the cor of secs. 11 & 12.

At point of intersection , I set a fir post, 3 ft. long 4" sq., 24" in the ground for closing cor. of secs. 13, & 14 mkd: CC T27S R2W S13 on E & S14 on W face with 1 groove on E & 5 grooves on W face, from which

- A fir, 18" dia. bears S.35°E. 72 lks. mkd: T27S R2W S13 BT
- A hemlock, 32" dia., bears S.37°45'W., 53 lks., mkd: T27S R2W S14 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - Nov. 1957 - C.S. File 49/28-3

Found - Original 18" now 24" Fir Stump S.35°E., 47.5 ft. I open & find good scribing "T27S"

Original 32" now 40" Hemlock stump S.37°45'W., 35.0 ft. shows scar, I do not open.

Set Brass Cap at corner mkd

Closing Cor. 11 | T27S R2W County
14 | 13 | Surveyors Office 1957

New BTs- 70" R.Fir Stump S.88°W., 67.0 ft. scribed S14 T27S R2W CS BT. No trees near in S.E.

Note - Distance between corners checks record distance. I find bearing to be S.86°E.

cont. next pg

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Closing Cor. Secs. 11, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Nov. 1968 - C.S. File 54/40-119

Found - 1957 CS Brass Cap in place.
70" R.Fir stump, good cond. burned, S.88°W., 67.0 ft. scribe visible.
Orig. now 24" Fir stump badly burned S.35°E., 47.5 ft. scribe visible.
Orig. now 40" Hemlock stump S.37¼°W., 35.0 ft. shows scar.
Set - 5/8" I.R. 10.0 ft. west & 5/8" I.R. 15.0 ft. West. 6.0 ft. steel fence post alongside brass cap.
The sec. cor. secs. 11 & 12 bears S.86°E., 71.9 ft.
This corner lies in dense greasewood brush in clear cut area.

Romanso E. Ware - For: US Forest Service - May 1977 - M65-20

Found - 1957 County Surveyors Office Brass cap with fence post alongside. 1957 & 1968
24" Fir stump bears S.35°E., 47.5 ft. visible scribing.
40" Hemlock stump bears S.37½°W. 33.0 ft visible scribing
70" Fir stump bears S.88°W. 67.0 ft visible scribing
New BTs- 6" Fir bears S.11°E., 44.8 ft. scribed "T27S R2W CC S13 BT".
7" Fir bears S.67°W., 61.5 ft. scribed "T27S R2W CC S14 BT".