

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

<p>GL0 survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4887)</p> <p>-----</p> <p>(1907) Set a basalt stone 15x11x6", 11" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which</p> <p> A chinquapin, 5" dia. bears S.27°W., 22 lks. mkd: ¼ S11 BT</p> <p> A fir, 7" dia., bears S.72°E., 52 lks., mkd: ¼ S12 BT.</p> <p>I destroy old ¼ sec. cor. & marks on BTs (1905)</p>
<p>Thomas E. Shrum, Jr. - For: US Plywood Corp. - April 17, 1963 - C.S. File 51/254-17 & M37-18</p> <p>-----</p> <p>Found - Orig. stone, ¼ on W face. 10" D.Fir S.72°E., 34.3 ft. dead & burned, but scribe visible. Chinquapin, Orig. BT, gone</p> <p>Set - 2½" alum. cap 8" Hemlock S.30°W., 26.3 ft. mkd: ¼ S11 BT. Nothing alive within limits to scribe in sec. 12.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Nov. 1968 - C.S. File 54/40-116</p> <p>-----</p> <p>Found - US Plywood alum. cap & BTs & old corner stone. 1963 Orig. 7" now 10" Fir, burned, S.72°E., 34.3 ft. Open higher & find scribe & reverse, dead snag (See Shrum's survey M37-18) 8" Hemlock S.30°W., 26.3 ft. scribed "¼ S11 BT"</p> <p>New BT - 10" Fir S.18°E., 3.9 ft. mkd: "¼ S12 CS BT" This corner lies on N-S cutting line, clear cut in sec. 12.</p>
<p>Loyd Moffit - For: US Forest Service - June 1986 - C.S. 62/30-28</p> <p>-----</p> <p>Found - A 2½" alum, cap on ¾" iron pipe with original corner stone along side. 1963 & 1968 A 10" fir (down and dead) bears S.72°E., 34.3 ft. scribe visible (OBT). A 14" fir bears S.18°E., 3.9 ft. scar visible. A 8" hemlock (down and dead) bears S.30°W., 26.3 ft. scribe visible.</p> <p>New BT - I marked a 12" cedar BT which bears S.28°W., 85.0 ft. from the corner, scribed ¼ S11 BT. Nailed A L.S. 944 brass washer to BT scribe.</p>