

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4876)

Set dogwood post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., marked on E & W faces 1/4 S from which
A fir, 20" dia., bears S.35°E., 27 lks., mkd: 1/4 S BT.
A cedar, 36" dia., bears S.50°E., 45 lks., mkd: 1/4 S BT.
No trees within limit on W

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Nov. 1968 - C.S. File 54/40-129

NOT FOUND
Old burn - NF by several others apparently by old chopped into trees.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #983, surveyed May/Aug 1979 - (DCSO records Vol. 44 Page(s) 16915-6)

Point for the 1/4 sec. cor. of secs. 1 & 2, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 1/2" dia., 22" in the ground with brass cap marked:

T27S R2W
1/4
S 2 | S 1
1979

from which
A fir, 18" dia., bears S.29°E., 30 lks., mkd: 1/4 S1 BT.
A fir, 13" dia., bears S.58 1/2°W., 19 1/2 lks., mkd: 1/4 S2 BT.

Fd. Ok by R. Geisler, M90-55 - 4/1984
fd. ok by R. Geisler, C.S. 63/34-23 - 5/1986