

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 10 Page(s) 4185)

Set Laurel post 4 ft. long, 4" sq., 24" in the ground for
cor. to secs. 1, 2, 35 and 36, mkd. T26S S36 on NE.; R2W S1
on SE.; T27S S2 on SW.; S35 on NW. faces, with 1 notch on E.
and 5 notches on W. edges, from which
A Laurel 8" dia., bears N.55°E., 30 lks. dist. mkd. T26S
R2W S36 BT.
A Laurel 10" dia., bears S.70°E., 30 lks. dist. mkd. T27S
R2W S1 BT.
A Fir 12" dia., bears S.30°W., 24 lks. mkd. T27S R2W S2 BT
A Fir 12" dia. bears N.14°W., 14 lks. mkd. T26S R2W S35 BT

GL0 Survey by Fred Mensch, U.S. Surveyor Under Special
Instructions dated May 25, 1916 - (DCSO records Vol. 10
Page(s) 4288)

Intersect the cor. of secs. 1, 2, 35 and 36, established by
Deputy Flint in 1882 and reestablished by U.S. Surveyor
Collier in 1913, which is a basalt stone, 5x8x7 ins. above
ground, firmly set, marked with 1 notch on E. and 5 notches
on W. edge, from which
A Fir 10" dia., bears N.39°30'E., 18 lks. dist. mkd. T26S
R2W S36 BT.
A Laurel 10" dia., bears S.70°E., 30 lks. dist. mkd. T27S
R2W S1 BT. (Orig. BT)
A Fir 20" dia., bears S.30°W., 24 lks. dist. mkd. T27S R2W
S2 BT. (orig. BT)
The original bearing tree on NW., a Fir 20" dia., which bears
from the cor. N.14°W., 14 lks. dist., is not in the section
to which it refers; therefore, I obliterate marks on this
tree and take new bearing tree in sec. 35 as follows:
A Fir 24" dia., bears N.30°W., 52 lks. dist. mkd. T26S R2W
S35 BT.

(Note: At this point in time (July 27, 1997) in the material
furnished me, I cannot find a Collier 1913 survey description
for this corner. V.Laugen)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
March 9, 1967 - C.S. File 54/40-5

Found - No trace of corner stone.
Orig. 12" now 21" Fir, alive, S.30°W., 15.8 ft.,
previously opened, face burned, fragmentary
scribe visible.
(Cont. Next Page)

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T26-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Orig. 10" now 19" Fir, alive, N.39½°E., 11.9 ft.,
previously opened. Open all of upper blaze and
find "T26S R2W S36" scribe.
Orig. 24" now 30" Fir, alive, N.30°W., 34.3 ft.,
shows good scar.
Orig. BT, N.11°W., 9.2 ft., obliterated by Mensch in
1916, alive, and opened to axe blaze.
Set Brass cap at cor. mkd: County Surveyors Office
T 26 S S 35 | S 36 R2W
T 27 S 1967 S 2 | S 1

New BTs- 16" D.Fir S.79½°E., 88.7 ft. mkd. T27S R2W S1 CS BT.
14" D.Fir N.4°E., 6.0 ft. mkd. T26S R2W S36 CS BT.
18" D.Fir S.19°W., 19.7 ft. mkd. T27S R2W S2 CS BT.
No trace of any other original BTs.

Fd. and used in BLM Resurvey by Wayne L. Rogers, Cadastral
Surveyor, under Group #983, Surveyed May/Aug. 1979 - (DCS0
records Vol. 43 Page(s) 16916-17)

Fd. OK, April 1984 by R. Geisler - M 90-55

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold,
Cadastral Surveyors & Robert H. Browning, Survey Technician,
under Group No. 1638, surveyed July 1992/April 1995 - (DCS0
records Vol. 51 (Page(s) 19743-4)

The cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.,
perpetuated by Tracy, in 1967, monumented with an iron post,
1" dia., firmly set, projecting 5" above the ground, with
brass cap (properly) mkd.
from which the remains of the original bearing trees
A fir, 25" dia., bears S.30°W., 24 lks., with a healed
blaze.
A fir stump, 22" dia., bears N.14°W., 14 lks., with a
healed blaze.
and a BT mkd. by Collier in 1913, and reported by Mensch
A fir, 25" dia. bears N.39½°E. 18 lks. with decayed blaze
and bearing trees mkd. by Tracy
A fir, 17" dia. bears N.3½°E. 8 lks. with healed dbl blaze
A fir, 19" dia bears S.84°E. 132 lks with healed dbl blaze
A fir, 27" dia. bears S.13°W. 30 lks with healed dbl blaze
No suitable bearing trees available NW. of the corner.

Fd. BC & 5 BTs by D. Edwards, 3/2008 - M155-16

continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyor's Office - Crew: Stephen J. Flaue and
Jeff Lorsung - 8/31/2020 - Filed 7/2025 - C.S. File 67/60-49

Condition Report only

Found - 2½" D.C.S.O. Brass cap
27" Fir S.30°W. 15.8 ft (Rec 24 lks)
30" Fir N.39½°E. 11.9 ft (Rec 18 lks)
21" Fir N.3½°E. 5.3 ft (Rec 8 lks)
23" Fir S.84°E. 87.1 ft (Rec 132 lks)
30" Fir S.13°W. 19.8 ft (Rec 30 lks)