

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4918)

-----  
Set a yew post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S25 on N & 36 on S face; from which  
A Hemlock, 10" dia. bears S.62°30'W. 13 lks. mkd: ¼ S36 BT  
A fir, 48" dia., bears N.21°W., 55 lks., mkd: ¼ S25 BT.  
East 3.00 chs - Derricks ¼ cor. which I now destroy bears N.300 lks. Note - We have no record of Derrick setting this corner.  
JC DCSO 7/2008

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - Oct/Nov. 1968 - C.S. File 54/40-106

-----  
Found - Orig. 10" now 12" Hemlock, alive, S.62½°W., 8.6 ft. open & find scribe marks.  
Orig. 48" Fir, now 50" stump, N.21°W., 36.3 ft. shows scar.  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R2W  
OFFICE ¼ S 25  
1968 S 36  
New BTs- 10" yew N.28°W., 25.3 ft. mkd: ¼ S25 CS BT.  
11" Hemlock S.53°W., 39.1 ft. mkd: ¼ S36 CS BT.  
This corner lies in shallow ravine, course West - Cut off in Sec. 25.