

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4921)

Set a Hemlock post, 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S24 on N & S25 face; from which
A fir, 55" dia., bears N.22°30'E., 36 lks., mkd: 1/4 S24 BT.
A fir, 18" dia., bears S.57°30'E., 60 lks., mkd: 1/4 S25 BT.
Could not find Derricks 1/4 sec. cor. after diligent search.
Note - We have no record of Derrick setting this corner.
JC DCSO 7/2008

Milo E. Godfrey, Deputy - Mike Stone - Sept. 7 1962 - C.S. File 49/28-7

Found - Fir, now 68" N.22½°E., 23.8 ft. Cut open & fd. good scribing "4 & BT"
W.Fir stump, now 25" S.57½°E., 39.6 ft. has been cut off below scribing, but lower part of face visible on stump.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R2W
OFFICE 1962 1/4 S24/S25
New BTs- 9" Yew N.17°W., 24.0 mkd: 1/4 S24 CS BT.
22" Hemlock S.65°W., 12.0 ft. mkd: 1/4 S25 CS BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - Oct/Nov. 1968 - C.S. File 54/40-111

Found - No trace of brass cap called for in 1962 ren.
Orig. 68" Fir, now sawed stump, N.22½°E., 23.8 ft.
9" Yew N.17°W., 24.0 ft., dying, scribe visible.
22" Hemlock S.65°W., 12.0 ft. now sawed stump, scribe visible.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R2W
(Set 6 ft. steel fence OFFICE 1968 1/4 S 24
post alongside BC) 1968 S 25
New BTs- 8" Hemlock N.43°W., 65.0 ft. mkd: 1/4 S24 CS BT
14" hemlock S.25°E., 53.3 ft. mkd: 1/4 S25 CS BT
This corner lies 2.0 ft. south of skid road in logged area.