

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4923)

-----  
Running East at 40.00 chs  
Point for 1/4 sec. cor. falls in a live Oak tree, 6" dia., I mark 1/4 S13 on N & 24 on S side, from which  
A live Oak, 6" dia. bears N.21°40'E., 3 lks. mkd: 1/4 S13 BT  
A fir, 8" dia., bears S.5°W., 23 lks., mkd: 1/4 S24 BT.  
43.00 chs - Derricks 1/4 sec. cor which I now destroy bears N 500 lks. Note - We have no record of Derrick setting this corner. JC DCSO 7/2008

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones & V. Perron - Nov. 1968 - C.S. File 54/40-112

-----  
Found - 6" now 10" Live Oak corner tree, open & find scribe & reverse.  
Orig. 6" now 11" Live Oak, N.21 3/4°E., 2.0 ft alive shows good scar.  
Orig. 8" now 17" Fir, alive, S.5°W., 15.2 ft., shows good scar.  
Set Brass cap under corner tree mkd: COUNTY SURVEYORS T27S R2W  
OFFICE 1/4 S 13  
1968 S 24  
New BTs- 8" R.Fir N.55°E., 8.0 ft. mkd: 1/4 S 13 CS BT  
Orig. 17" D.Fir S.5°W., 15.2 ft. mkd: 1/4 S24 CS BT  
(above old scar)  
This corner lies 15 ft E of top of 75 ft high vertical bluff

Loyd Moffit - For: US Forest Service - June 1986 - C.S. 62/30-29

-----  
Found - 1968 County Surveyor's brass cap on a 1" IP exposed 12" set under the original oak corner tree. (No scribes visible on tree). 1968  
8" fir snag bears N.55°E., 8.0 ft. scribe visible.  
18" fir bears S.05°W., 15.2 ft. scribe visible.  
New BT - I marked a 32" fir BT which bears N.86°E., 57.1 ft. from the corner, scribed 1/4 S13 BT. Nailed L.S. 944 brass washer to BT scribe