

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 13 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4886)</p> <p>-----</p> <p>Set a basalt stone 13x7x6", 9" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which</p> <p> A fir, 28" dia., bears N.54°W., 34 lks., mkd: ¼ S12 BT.</p> <p> A fir, 36" dia., bears S.79°W., 58 lks., mkd: ¼ S13 BT.</p>
<p>GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4913)</p> <p>-----</p> <p>Intersect the ¼ sec. cor. which is a stone, firmly set, marked & witnessed as described by the surveyor general & which I now change to refer to sec. 12 only.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Nov. 1968 - C.S. File 54/40-109</p> <p>-----</p> <p>We find US Plywood alum. cap mkd 13 only No BTs. S 1/4 Cor. sec. 12 only bears S.89°E., 141.4 ft.</p>
<p>Romanso E. Ware - For: US Forest Service - May 1977 - M65-20</p> <p>-----</p> <p>Found - Alum. cap on rod. Un-recorded.</p> <p>Set - Re-proportion & set 2½" IP with brass cap 0.86 ft. East of un-recorded alum. cap. Bras cap stamped T27S R2W ¼ S13 1977 LS 1005.</p> <p>New BTs- 8" alder bears S.34°E., 15 ft. scribed "¼ S13 BT" 12" Hemlock bears S.88°W., 38.1 ft. scribed "¼ S13 BT"</p> <p>Trees with washers in BT face.</p>
<p>Jim Landrum, USFS - Leonard Herzstein - May 17, 1982 - C.S. 61/32-6</p> <p>-----</p> <p>Found - 2½" diam. I.P. with properly mkd brass cap, firmly set, flush with 2 ft. dia. mound of stone. 1977</p> <p>1" I.R. with alum cap projecting 8" above 2 ft. dia mound of stone mkd U.S. P.C. bears west 0.86 ft.</p> <p>4"x4" wooden post bears 3 ft. west.</p> <p>8" alder, S.34°E., 15.0 ft. with fragmentary scribe marks & alum. washer visible on partly healed double blaze. 1977</p> <p>12" hemlock S.88°W., 38.1 ft. with fragmentary scribe marks & alum, washer visible on partly healed double blaze. 1977</p> <p style="text-align: right;">cont. next pg</p>

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set - 6 ft. steel fence post East 2 ft.
This corner lies on east edge of old dirt road, now
undergoing new road construction.