

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4874-5)</p> <p>-----</p> <p>Set maple post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., marked on N & S faces 1/4 S; from which A fir, 8" dia., bears N.50°W., 6 lks., mkd: 1/4 S BT. A fir, 20" dia., bears S.45°E., 15 lks., mkd: 1/4 S BT.</p>
<p>GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4885 & 4896)</p> <p>-----</p> <p>Pg 4885 & 4896 1/4 Cor., which is a post 3" sq., 2 ft. above the ground, witnessed & marked as described by the Surveyor General.</p>
<p>Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - Nov. 8, 1957 - C.S. File 49/28-4</p> <p>-----</p> <p>Found - Old 4"x4" sq. stake at cor. & orig. 8" now 16" W.Fir N.50°W., 4.0 ft. This BT previously opened (partly) I open lower portion & find good scribing "BT". Upper section show scribing "S" I can find no trace of orig. SE BT. Set brass cap at corner mkd: 1/4 S 1 T27S R2W County Surveyors S 12 Office 1957 New BTs- 10" W.Fir S.14°W., 15.7 ft. scribed 1/4 S12 CS BT. 14" R.Fir N.30 1/2°E., 17.4 ft. scribed 1/4 S 1 CS BT. ("BT" bark scribed)</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & E. West - March 9, 1967 - C.S. File 54/40-4</p> <p>-----</p> <p>Found - 1957 Co. Surv. Brass cap & BTs. (1957) 10" now 11" W.Fir S.14°W., 15.7 ft. Alive, blaze nearly healed 14" Fir now down, N.30 1/2°E., 17.4 ft. scribes visible. Orig. 8", now 17" Fir, alive, N.50°W., 4.0 ft. scribe visible. New BT - 16" W.Fir N.70 1/2°W., 6.2 ft. mkd: 1/4 S1 CS BT. Note - This corner lies 200 ft. west of Little River Road.</p>
<p>Fd. Ok by DCSO VRT Nov. 1968 - C.S. File 54/40</p>
<p>Romanso Ware - For: US Forest Service - March 1977 - M65-13</p> <p>-----</p> <p>Found - Brass cap, properly mkd. continued next page</p>

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

10" D.Fir snag S.9°W., 15.4 ft. (good scar)
16" W.Fir N.78°W., 6.3 ft. (good scar)
16" W.Fir N.39°W., 4.5 ft. (open face)
New BTs- 12" Maple S.45°E., 17.0 ft., scribed "¼ S12 BT"
w/washer in BT face.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - Dec. 11, 1985 - C.S. File 62/21-23

Found - 1957 County brass disk on a I.P. protruding 10" above ground.
Orig. BT, 18" now a 17" dia. W.Fir with an opened blaze, scribing visible "S" bears N.42½°W., 4.5 ft. (Rec. N.39°W.)
14" Fir now down and rotted, no scribing visible. Root hole bears N.30½°E., 17.4 ft. 1957
SW BT per 1957 Ren. not found.
A 16" W.Fir with a double well healed blaze bears N.70½°W., 6.3 ft (Rec. per 1977 ren N.78°W.) 1966
A 12" maple with a partially healed double blaze, scribing visible "¼ S12 BT" and an alum. washer in bottom blaze marked "LS 1005" bears S.49°E., 16.4 ft. (Rec. S.45°E., 17.0 ft.) 1977
New BT - A 6" W. fir double blazed and scribed "¼ S12 CS BT" bears S.27°W., 54.3 ft.
Corner is approx. 200 ft. south of Littler River Road.