

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 641500

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 12 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO rec Vol 12 Pg 4886)  
-----  
Set a basalt stone 13x7x6", 9" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
    A fir, 28" dia., bears N.54°W., 34 lks., mkd: ¼ S12 BT.  
    A fir, 36" dia., bears S.79°W., 58 lks., mkd: ¼ S13 BT.

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4913)  
-----  
Intersect the ¼ sec. cor. which is a stone, firmly set, marked & witnessed as described by the surveyor general & which I now change to refer to sec. 12 only.

Thomas E. Shrum, Jr. - For: US Plywood Corp. - April 1963 - C.S. File 51/254-17  
-----  
Found - Orig. stone - ¼ N face.  
        48" D.Fir S.79°W., 38.4 ft. (Orig. good condition)  
        37" D.Fir snag, N.54°W., 22.3 ft. (Orig.)  
        Aluminum reference tag S.76°E., 7.9 ft. 1952  
Set - 2½" Alum cap  
      10" Sugar pine N.17°E., 26.2 ft. mkd: ¼ S12 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Nov. 1968 - C.S. File 54/40-109  
-----  
We find US Plywood alum cap set from OBTs - we find scribe on SE also new BT. 12" Pine N.17½°E., 25.8 ft. scribe visible on nearly healed blaze. From this corner we find US Plywood alum. cap mkd 13 only No BTs.  
N 1/4 Cor. sec. 13 only bears N.89°W., 141.4 ft.

Gerald Nygren - For: Seneca Jones Tmbr Co - 7/2018 - M174-54  
-----  
Found - U.S. Plywood Corp. Aluminum cap  
        (1904) 36" D.Fir, now 48" bears S.79°W., 38.4' healed blaze  
        36" D.Fir, now 37" snag bears N.54°W., 22.3' healed blaze  
        (1963) 10" S.Pine, now blowdown, roothole bears N.17°E., 26.2'  
        1977 brass cap for the 1/4 cor. Of sec. 13 only per M65-20, bears S.89°56'03"W., 143.93' (N.89°58'20"E, 144.04) {S89°58'14"E, 143.18'}