

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 676100

PRIMARY CORNER DESCRIPTION C C Sec. 1, T28-2; & S. 6, T28-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5372)

(At a point 6.44 chs. West of the standard cor. of T27S Rs. 1 and 2)
Set a basalt stone 15x12x8 ins., 10" in ground for cor. of T28S Rs. 1 and 2 W., marked C C on S. and 6 notches on SE. and W. edges; from which
A Fir 18" dia., bears S.71°E., 75 lks. dist. mkd. T28S R1W S6 BT.
A Fir 12" dia., bears S.79°W., 63 lks. dist. mkd. T28S R2W S1 BT.

GLO Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4902)

No trace of closing cor. of T28S., Rs. 1 and 2 W., can be found after diligent search.

Fd. and used in GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5490-91)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 1968 - C.S. File 54/40-89

Found - Do not find Corner stone called for at closing cor.
Orig. 18" now 36" Fir, alive, S.71°E., 49.5 ft., shows good scar.
Orig. 12" now 24" Fir, alive, S.79°W., 41.6 ft., shows good scar. We open to find scribe marks.
Set Brass cap at cor. mkd: County Surveyors Office
T27S R2W S 1 | S 6 R1W
T28S 1968
New BTs- 20" D.Fir S.10°W., 7.9 ft. mkd. T28S R2W S1 CC CS BT
14" D.Fir S.42°E., 14.2 ft. mkd. T28S R1W S6 CC CS BT.
This corner lies on steep SW. slope about 413 ft. W. of stand. cor. of T27S Rs. 1 and 1 W.