

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882 - (DCSO records Vol. 12 Page(s) 4873-74)

Set Yew post for ¼ sec. cor. 3 ft. long, 3" sq., 24" in the ground marked ¼ S on E. and W. faces, from which
A Hemlock 24' dia., bears S.30°E., 13 lks. dist. mkd. ¼ S BT.
A Hemlock 14" dia., bears S.45°W., 53 lks. dist. mkd. ¼ S BT.

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4780)

Set basalt stone 18x10x5 ins., 14" in the ground for ¼ sec. cor. marked ¼ on W. face, from which
A Fir 14" dia., bears S.49°E., 78 lks. dist. mkd. ¼ S31 BT.
A Hemlock 20" dia., bears N.78°W., 104 lks. dist. mkd. ¼ S36 BT.
From this cor., the old cor. bears West 3.00 chs. I destroy all traces of the old cor.

Tied corner in GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4908)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Sept/Oct. 1968 - C.S. File 54/40-88

Found - Corner Stone mkd. "¼" on W. face, firmly set at corner point.
Orig. 14" now 36" Hemlock, alive, S.49°E., 51.5 ft. shows faint scar. Recorded to be Fir. Rescribe "¼ S31 CS BT".
Orig. 20" now 40" Hemlock, alive, N.78°W., 68.6 ft., shows "¼" on open blaze. Rescribe "¼ S36 CS BT".
Set Brass cap at cor. mkd: County Surveyors Office
(Reset Stone alongside) T 27 S
R2W ¼ S 36 | S 31 R1W
1968

This corner falls 50 ft. N. of small creek, course NW. in dense thicket of vinemapple. No smaller trees near to scribe for BTs.