

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 30 only, T27-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by S.C. Flint, Contract #459, dated August 3, 1882 - (DCSO records Vol. 12 Page(s) 4873)</p> <p>-----</p> <p>Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on E. and W. faces, from which</p> <p style="padding-left: 40px;">A Cedar 7" dia., bears S.75°W., 12 lks. dist., mkd. ¼ S BT</p> <p style="padding-left: 40px;">A Cedar 36" dia., bears S.40°E., 30 lks. dist., mkd. ¼ S BT.</p>
<p>GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4781-82)</p> <p>-----</p> <p>Set basalt stone 16x10x5 ins., 11" in the ground for ¼ sec. cor., mkd. ¼ on W. face, from which</p> <p style="padding-left: 40px;">A Cedar 18" dia., bears N.16°E., 46 lks. dist. mkd. ¼ S30 BT.</p> <p style="padding-left: 40px;">A Cedar 20" dia., bears N.41°W., 36 lks. dist. mkd. ¼ S25 BT.</p> <p>From this cor. the old ¼ sec. cor. bears N.87½°W., 2.20 chs. dist. I destroy the old cor.</p>
<p>GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4908)</p> <p>-----</p> <p>The ¼ sec. cor. which is a stone, firmly set, mkd. and witnessed as described by the surveyor general and which I now change to refer to sec. 30 T27S R1W only.</p>
<p>Survey by Ronald A. Quimby - For: U.S. Forest Service - May 1980 - M 83-78</p> <p>-----</p> <p>Set 2½" Iron pipe with brass cap mkd. "T27S R1W S30 only RLS 1654 1980.", from which</p> <p style="padding-left: 40px;">6" Cedar bears S.64°W., 15.8 ft. scribed "¼ S30 BT".</p> <p style="padding-left: 40px;">7" Hemlock bears N.9°W., 17.8 ft. scribed "¼ S30 BT"</p> <p style="padding-left: 40px;">16" Hemlock bears S.44°E., 19.9 ft. scribed "¼ S30 BT"</p> <p>Brass washers mkd. RLS #1654 set in BT faces. Also set post and sign 4.5 ft. North.</p>
<p>Gerald V. Nygren, LS 1035 - Oct. 1988 - C.S. File 63/69-31</p> <p>-----</p> <p>Found - 2½" Iron pipe with brass cap.</p> <p style="padding-left: 40px;">An 8" Cedar bears S.64°W., 15.8 ft., visible scribing. (Cont. Next Page)</p>

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 700241

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 30 only, T27-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An 8" Hemlock bears N.9°W., 17.8 ft., visible scribing.
A 16" Hemlock stump bears S.44°E., 19.9 ft. visible scribing.
New BT - A 7" Cedar bears S.25°E., 14.9 ft. scribed "¼ S30 BT". Set ½" brass washer in BT face mkd. "LS 1035".