

PRIMARY CORNER DESCRIPTION C C for Secs. 19 & 30 only, T27-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 12 Page(s) 4872)

Set Chinquapin post 4 ft. long, 4" sq., 24" in the ground for
cor. to secs. 24, 25, 19 and 30, and marked T27S S19 on NE.;
R1W S30 on SE.; R2W S25 on SW. and S24 on NW. faces, with 4
notches on the N. and 2 on the S. edges, from which
A Fir 8" dia., bears N.50°E., 9 lks. dist. mkd. T27S R1W
S19 BT.
A Fir 8" dia., bears S.15°E., 32 lks. dist. mkd. T27S R1W
S30 BT.
A Chinquapin 12" dia., bears N.15°W., 16 lks. dist. mkd.
T27S R2W S24 BT.
A Fir 30" dia., bears S.60°W., 15 lks. dist. mkd. T27S R2W
S25 BT.

GLO survey by Homer D. Angell, Deputy Surveyor, under
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11
Page(s) 4782)

Set basalt stone 20x12x8 ins., 15" in the ground for cor. of
secs.19, 24, 25 and 30 marked with 4 notches on the N. and 2
notches on the S. edges, from which
A Hemlock 14" dia., bears N.65°E., 18 lks. dist. mkd. T27S
R1W S19 BT.
A Hemlock 8" dia., bears S.40½°E., 26 lks. dist. mkd. T27S
R1W S30 BT.
A Fir 14" dia., bears S.47½°W., 55 lks. dist. mkd. T27S
R2W S25 BT.
A Dogwood 10" dia., bears N.31½°W., 20 lks. dist. mkd.
T27S R2W S24 BT.
From this cor., the old sec. cor. bears N.83°40'W., 2.31 chs.
dist. I destroy the cor.

GLO survey by Morris Wygant, compassman for Zachariah M.
Derrick, U.S. Deputy Surveyor, under Contract #779, dated
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4909)

The cor. of secs. 24, 25, 19 and 30, which is a stone firmly
set, marked and witnessed as described by the surveyor
general, and which I now change to refer to secs. 19 and 30,
T27S R1W, only, bears West 91 lks. dist.

(Cont. Next Page)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Douglas Co. Surveyors Office - L.E. Monrean; P.L. Earle; A.V. Cangie - June 19, 1975 - C.S. File 57/30-12

Found - 16"x10"x8" stone with 4 notches on one edge and 2 notches on the opposite edge, lying on surface of ground.

A rotted stump bears N.65°E., 8.5 ft. (Rec. 11.9 ft.), no scribing.

A Fir stump bears S.42°W., 37.7 ft. (42" Fir snag stands directly on line and scribed as BT for closing corner to the South) (Rec. 36.6 ft.)

Set Brass cap at cor. mkd: County Surveyors Office

	T27S R1W
R2W	S 19
S 24	S 30
	1975

Set original stone on easterly edge of cap.

New BTs- A 14" dia. Hemlock bears N.21°E., 48.5 ft. scribed "T27S R1W S19 CS BT."

A 16" dia. Hemlock bears S.71°E., 28.3 ft. scribed "T27S R1W S30 CS BT."

John Ransom, USFS - Jonathan Drew - 10/2010 - CS File 65/72-14

Found - 2¼" Brass Cap on 1" Iron Pipe, Projecting 4" above ground cap mkd "County Surveyors Office T27S R2W R1W 524 519 530 1975" Section Corner for 19+30 ONLY

26" Hemlock S.71°E., 28.3 ft. Part. Healed Double Blaze, "BT" visible

INDT Hemlock N.21°E., 48.5 ft. Windfall Lays east, Part. Healed Double Blaze

Fir Stump S.38°E., 24.4 ft. Record stump not found, area is heavy brush/slash/duff from PVT logging

Brass Cap S.7°6'20"E., 58.61 ft. Section Corner for S24+S25 ONLY

New - Painted 6" Band around BTs and painted face blazes, new nails on signs, cleared brush around corner
 Added new tree:

6" Fir Bears N.51°30'E., 22.1 ft. Scribed "X" "BT" on double blaze

No suitable trees to the West in clearcut.

New tree measured w/staff compass (15.75° DEC) /tape.

Remarks- Found Steel Post 1.8 FT. North w/1' Property Boundary Sign. Drove Aluminum Post 2.0 FT. South w/ Property Boundary and Land Survey Monument Signs
 Line maintained to North .5 MI cont. next pg.

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 700301

PRIMARY CORNER DESCRIPTION C C for Secs. 19 & 30 only, T27-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Note - Corner falls on east slope on edge of fresh <10 yr old PVT clearcut Falls just east of break where level land begins to slope east. Take 2792 to 040 spur, then take 200 spur to Alum. Post where line crosses, follow posted! blazed line south to corner.

Area where corner falls is heavy brush

PLANE COORDINATE POSITION DATA

State OR	Zone UTM-10M
North	4782830
East	510384
Estab. By	GCDB