

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION C C for Secs. 13 & 24 only, (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4924)

At point of intersection (140 lks. S.0°4'E. of cor. of secs. 18 & 19) I set a Cedar post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 13 and 24, marked CC T27S R2W on W.; S13 on N. and S24 on S. face with 3 grooves on N. and S. faces, from which

A Cedar 24" dia., bears N.67°45'W., 38 lks. dist. mkd. T27S R2W S13 BT.

A Chinquapin 8" dia., bears S.35°30'W., 38 lks. dist. mkd. T27S R2W S24 BT.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4910)

Derrick's closing cor. for secs. 13 and 24 which is a stone, firmly set, marked and witnessed as described by him. I destroy this cor.

Survey by Romanso E. Ware - For: U.S. Forest Service - May 1977 - M 65-19

Set a 2½" Iron pipe with brass cap in rock mound stamped "T27S R2W CC S13 S24 S19 R1W LS 1005 1977."

New BTs- 7" Maple bears N.2°W., 52.2 ft. scribed T27S R2W S13 CC BT.

8" Maple bears South, 45.9 ft. scribed T27S R2W S24 CC BT.