

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 700402

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only, T27-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 12 Page(s) 4871-72)

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor.
to secs. 18, 19, 13 and 24 marked T27S S18 on NE.; R1W S19 on
SE.; R2W S24 on SW. and S13 on NW. faces, with 3 notches on
N. and S. edges, from which
A Fir 6" dia., bears N.58°E., 33 lks. dist. mkd. T27S R1W
S18 BT.
A Cedar 10" dia., bears S.39°E., 32 lks. dist. mkd. T27S
R1W S19 BT.
A Fir 48" dia., bears S.65°W., 9 lks. dist. mkd. T27S R2W
S24 BT.
A Fir 50" dia., bears N.20°W., 74 lks. dist. mkd. mkd.
T27S R2W S13 BT.

GLO survey by Homer D. Angell, Deputy Surveyor, under
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11
Page(s) 4783)

Set basalt stone 20x10x10 ins., 15" in ground for cor. of
secs. 13, 18, 19 and 24 marked with 3 notches on N. and S.
edges, from which
A Fir 10" dia., bears N.21°E., 27 lks. dist. mkd. T27S R1W
S18 BT.
A Hemlock 24" dia., bears S.26°E., 13 lks. dist. mkd. T27S
R1W S19 BT.
A Hemlock 12" dia., bears S.18°W., 53 lks. dist. mkd. T27S
R2W S24 BT.
A Cedar 30" dia., bears N.63°W., 36 lks. dist. mkd. T27S
R2W S13 BT.
From this cor. the old sec. cor. bears N.49°35'W., 4.26 chs.
dist. I destroy the old cor.

GLO survey by Morris Wygant, compassman for Zachariah M.
Derrick, U.S. Deputy Surveyor, under Contract #779, dated
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4909)

The cor. of secs. 13 and 18, 19 and 24, which is a stone,
firmly set, marked and witnessed as described by the surveyor
general, and which I now change to refer to secs. 18 and 19,
T27S R1W only, bears West 10 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Wm.
Stoffell; M. Stone, crew - July 2, 1964 - C.S. File 49/28-18

Found - 24" Hemlock snag, S.26°E., 8.6 ft., face badly
badly burned, no scribing vis. (Cont. Next Page)

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 700402

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only, T27-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Uprooted Fir snag, N.21°E., 17.8 ft., cut open and found good scribing "S". Could not tell where tree had stood.
Portion of large Cedar stump with root system still in ground, N.63°W., 23.8 ft., no markings.
Did not find original SW. BT.
Set 3/4" Iron rod, corner position falls under log, approx. 40" dia.
Rescribe-Hemlock snag, S.26°E., 8.6 ft. "T27S R1W S19 CS BT"
New BT - 40" D.Fir stump N.34°E., 60.0 ft. mkd. "T27S R1W S18 CS BT".
No live trees available. Corner is in clear cut logged area.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Nov. 1968 - C.S. File 54/40-114

Found - 3/4" Iron rod under 40" log.
40" Fir stump, N.34°E., 60 ft.
24" Hemlock snag, now down and only decayed remains of stump in place, we saw 40 out.
Set Brass cap at cor. mkd: County Surveyors Office

R	T 27 S	R
2	S 18	1
W	S 19	W
	1968	

Reset I.R. alongside and set 6 ft. steel fence post.
No trees or stumps available for bearing trees.
Corner lies approx. 125 ft. West of Rd. #274L in logged off area, now densely covered with greasewood brush.

Fd. Corner and ADDED BLM 1971 to DCSO brass cap - BLM resurvey by Jasper M. Sams and Donevan C. Harris, Cadastral Surveyors, Group #747, Surveyed June/Aug. 1971 - (DCSO records Vol. 35 Page(s) 14577-78) (This survey suspended May 22, 1980)

Survey by Romanso E. Ware - For: U.S. Forest Service - May 1977 - M 65-20

Found - 1968 DCSO brass cap re-stamped "BLM 1971" on a 1" I.P. with 3/4" Iron rod, bears 0.5 ft. West.
32" Fir stump bears N.34°E., 60.0 ft. scribed "T27S R1W S18 CS BT."
New BTs- 10" Maple bears S.45°E., 50.5 ft. scribed T27S R1W S19 BT.
6" Fir bears N.52°E., 43.6 ft. "T27S R1W S18 BT."

(Cont. Next Page)

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 700402

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, T27-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #747, surveyed June 1980 - (DCSO records Vol. 42 Page(s) 16469-70)

(CORNER REPORT)

The Sec. cor., perpetuated and recorded by Tracy in 1968, and further perpetuated and recorded by Ware in 1977, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground and marked as in 1968 with BLM 1971 added

from which the remains of an original bearing tree

A Hemlock stump size indeterminate, bears S.26°E., 13 lks. dist., no marks visible.

and the remains of a bearing tree mkd. by Tracy:

A Fir stump 40" dia., bears N.36°E., 90 lks. dist. with scribe marks T27S R1W S18 CS BT visible on open blaze.

and bearing trees mkd. by Ware:

A Fir 8" dia., bears N.49½°E., 64 lks. dist., with scribe marks S R W S18 T visible on open blaze.

A Maple 12" dia., bears S.47½°E., 75 lks. dist., with scribe marks T27S R1W S19 BT visible on open double blaze.