

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only, T27-1

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GL0 survey by S.C. Flint, Contract #459, dated August 3, 1882 - (DCSO records Vol. 12 Page(s) 4871)

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 12, 13, 7 and 18, marked T27S S7 on NE.; R1W S18 on SE.; R2W S13 on SW.; and S12 on NW. faces, with 2 notches on the N. and 4 on S. edges, from which
A Fir 36" dia., bears N.20°E., 39 lks. dist. mkd. T27S R1W S7 BT.
A Fir 6" dia., bears S.88°E., 23 lks. dist. mkd. T27S R1W S18 BT.
A Cedar 36" dia., bears N.40°W., 34 lks. dist. mkd. T27S R2W S13 BT.
A Fir 5" dia., bears N.49°W., 44 lks. dist. mkd. T27S R2W S12 BT.

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4783-84)

Set a basalt stone 15x10x8 ins., 10" in ground for cor. of secs. 7, 12, 13 and 18, marked with 2 notches on N. and 4 notches on S. edges, from which
A Fir 12" dia., bears N.64°E., 42 lks. dist. mkd. T27S R1W S7 BT.
A Pine 14" dia., bears S.22°E., 46 lks. dist. mkd. T27S R1W S18 BT.
A Pine 16" dia., bears S.5°W., 31 lks. dist. mkd. T27S R2W S13 BT.
A Pine 20" dia., bears N.57½°W., 42 lks. dist. mkd. T27S R2W S12 BT.
From this cor., old sec. cor. bears N.22°4'W., 5.96 chs. dist. I destroy this cor.

GL0 survey by Charles E. Roberts, U.S. Deputy Surveyor, under Contract #759, dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4884 3/4)

The cor. of secs. 7 and 18, T27S R1W which is a basalt stone, 8x7x6 ins. above the ground, marked and witnessed as described by the surveyor general, bears South 10.10 chs. (from cor. of 12 & 13, T27S R2W). I destroy marks on bearing trees referring to secs. 12 and 13.

Used corner in GL0 survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4910) (Cont. Next Page)

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 700472

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only, T27-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Wm. Stoffel; M. Stone, crew - Dec. 1963 - C.S. File 49/28-17

Found - 36" Sugar Pine, S.22°E., 30.4 ft., opened and found good scribing.

No trace of any other bearing tree.

Did not find rock at corner.

Set Brass cap at cor. mkd: County Surveyors Office

T 27 S
R2W | S 7 R1W
 | S 18
 1963

New BTs- 18" D.Fir N.11°E., 35.5 ft. mkd. T27S R1W S7 CS BT

16" Red Cedar S.67°E., 29.4 ft. mkd. T27S R1W S18 CS BT.

This corner is approx. 10 chains South of cor. secs. 12 & 13, T27-2.

Fd. OK, Nov. 1968 by V. Tracy, DCSO - C.S. File 54/40-118