

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION C C for Secs. 12 & 13 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Charles E. Roberts, U.S. Deputy Surveyor, under Contract #759, dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4884 3/4)

Set a basalt stone 15x8x6 ins., 10" in the ground, for cor. of secs. 12 and 13, marked with 4 notches on S. and 2 notches on N. edge, from which
A Cedar 7" dia., bears S.38°W., 31 lks. dist. mkd. T27S R2W S13 BT.
A Fir 50" dia., bears N.40°W., 35 lks. dist. mkd. T27S R2W S12 BT.

Fd. Corner OK, in GL0 survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4910)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Wm. Stoffel; M. Stone, crew - Dec. 1963 - C.S. File 49/28-15

Found - Rock, 15"x8"x6" with 2 notches on one side and 4 notches on opposite side, lying loose on top of ground near corner.
11" Red Cedar S.30°W., 20.5 ft. has been previously opened, good scribing.
Stump of 50" Fir, N.40°W., 23.1 ft., scar visible.
Set Brass cap at cor. mkd: County Surveyors Office
T 27 S
R2W S 12 | R1W
S 13 |
1963

Deposit corner stone alongside.
New BTs- 15" Red Cedar N.14°W., 66.3 ft. mkd. T27S R2W S12 CS BT.
12" D.Fir S.60°W., 9.6 ft. mkd. T27S R2W S13 CS BT.
Corner lies approx. 200 ft. N. of rocked logging road, running NW. and SE.

Fd. OK, Nov. 1968 by V. Tracy, DCSO - C.S. File 54/40-118