

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only, T27-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 12 Page(s) 4870)

Set Maple post 3 ft. long, 3" sq., 24" in the ground for ¼
sec. corner marked on E. and W. faces "¼ S", from which
A Fir 24" dia., bears N.40°W., 25 lks. dist. mkd. ¼ S BT
A Maple 8' dia., bears N.80°E., 22 lks. dist. mkd. ¼ S BT

GLO survey by Homer D. Angell, Deputy Surveyor, under
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11
Page(s) 4784)

Set basalt stone 15x14x8 ins., 10" in ground for ¼ sec. cor.
marked ¼ on W. face, from which
A Pine 24" dia., bears S.18°E., 65 lks. dist. mkd. ¼ S7 BT
A Pine 24" dia., bears N.31°W., 84 lks. dist. mkd. ¼ S12
BT.
From this cor., the old cor. bears N.9°29'W., 6.43 chs. dist.
I destroy the old cor.

GLO survey by Charles E. Roberts, U.S. Deputy Surveyor, under
Contract #759, dated Oct. 26, 1904 - (DCSO records Vol. 12
Page(s) 4884½)

Intersect ¼ sec.cor. to sec. 7, T27S R1W which is a basalt
stone, 7x7x12 ins. above ground, marked and witnessed as
described by the surveyor general.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Oct. 1968 - C.S. File 54/40-97

Found - Corner stone mkd. "X" on top and "¼" on W. face,
firmly set.
Orig. 24" now 38" Pine, alive, S.18°E., 42.9 ft.,
open and find scribe.
Orig. 24" now 30" Pine stump, N.31°W., 55.4 ft. open
and find scribe.

Set Brass cap at cor. mkd: County Surveyors Office
T 27 S
R2W | ¼ S7 R1W
1968

Set old corner stone alongside.
New BTs- 13" W.Fir S.24°E., 12.0 ft. mkd. ¼ S7 CS BT.
11" W.Fir N.52°E., 16.8 ft. mkd. ¼ S7 CS BT.

(Cont. Next Page)

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 700531

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only, T27-1

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Survey by Romanso E. Ware - For: U.S. Forest Service - July
1980 - M 79-50

Found - 1968 DCSO brass cap.
12" Fir, N.52°E., 16.8 ft., scar.
16" Fir, S.24°E., 12.0 ft., scar.
24" Fir, S.18°E., 42.9 ft., visible scribes.
Set post and sign 5.0 ft. North.