

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Charles E. Roberts, U.S. Deputy Surveyor, under Contract #759, dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4884½)

 Set a basalt stone 18x12x12 ins., 12" in the ground for ¼ sec. cor. marked ¼ on W. face, from which
 A Fir 16" dia., bears N.60°W., 25 lks. dist. mkd. ¼ S12 BT
 A Fir 20" dia., bears S.68°W., 28 lks. dist. mkd. ¼ S12 BT

Baughman Surveying - For: Cal Willis - Feb. 1974 - M 52-77

 Set Brass cap, from which
 12" Fir scribed ¼ S12 BT, N.4°W., 19.0 ft.
 6" Fir scribed ¼ S12 BT, S.49°W., 44.8 ft.

On survey map M 65-13, March 1977, "Set new BT tags."

Douglas Co. Surveyors Office - Randall Smith and Terrie Franssen, crew - July 1, 1991 - C.S. File 64/17-1

 Found - A 2½" dia. brass cap on a 1¼" O.D. Iron pipe leaning South of plumb, protrudes 12" above ground.
 12" now 16" dia. D.Fir with a fully healed single blaze, bears N.4°W., 18.6 ft. (Rec. N.4°W., 19.0 ft. is a slope measurement.)
 6" now 9" dia. D.Fir with a fully healed single blaze, bears S.49°W., 46.8 ft. (Rec. S.49°W., 44.8 ft.)

Returned Brass cap/Iron pipe to plumb position, protrudes 2" above a 2 ft. dia. mound of stone.

New BTs- 5" dia. Cedar, double blazed and scribed "¼ S12 CS BT", bears N.41½°W., 15.8 ft.

8" dia. D.Fir, double blazed and scribed "¼ S12 CS BT" bears S.63°W., 51.7 ft.

BC/IP is in a cut bank on the N. side of a gravel road, 25 ft. from centerline.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - June 3, 1993 - C.S. File 64/43-31

 Found - 2½" dia. Brass cap. on a 1¼" O.D. iron pipe, protrudes 2" above a 2 ft. dia. mound of stone.
 12" now 16" dia. D.Fir with a fully healed single blaze bears N.4°W., 18.0 ft. (rec. N.4°W., 18.6 ft.)

5" now 5" dia. Cedar with a partially healed double blaze, scribing visible "¼ S12 CS BT" bears N.41½°W., 15.8 ft. (Cont. Next Page)

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BT's in slide area -

6" now 10" dia. D.Fir with a fully healed single blaze, bears S.50½°W., 48.6 ft. (rec. S.49°W., 46.8 ft.)

8" now 8" dia. D.Fir with a partially healed double blaze, scribing visible "¼ S12 CS BT" bears S.62°W., 54.2 ft.

32" dia. D.Fir with BT tag on ground numerous axe mark and blazes or scribing dated by ring count approx. 30 yrs old. Tag marked "¼ S12 only on new BT Hendrikson S.33°W., 56.8 ft" bears S.37½°W., 66.5 ft. (unrecorded BT?)

New Accessories -

20" dia. D.Fir double blazed and scribed "¼ S12 CS BT" bears N.82°W., 118.3 ft.

10" dia. Cedar double blazed and scribed "¼ S12 CS BT" bears N.43½°W., 37.7 ft.