

TOWNSHIP 27 RANGE 03E POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Township Corner

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10377

-----  
Set an iron post, 3 ft. long, 3" dia., 27" in the ground, for standard cor. of Tps 27 S, Rs. 2 and 3 E, with brass cap mkd.

S C  
T27S  
R2E|R3E  
S 36|S 31  
1927

from which

A fir, 36" dia., bears N.35°E., 62 lks., mkd: T27S R3E S31  
S C BT.

A fir, 36" dia., bears N.35°W., 72 lks., mkd: T27S R2E S36  
S C BT.

NOTE: See GLO Survey by Samuel C. Flint, Under Contract #473, dated June 5, 1883 (DCSO Records Vol. 24 Page(s) 10361) for Township corner that was destroyed by Lincoln Wilkes