

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 24; 18 & 19 T27-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 23 Page(s) 9948)

Set an iron post, 3 ft. long, 2" dia., 22" in the ground, to bedrock, and mound of stone, 3 ft. base, 1 ft. high, for the cor. of secs. 13, 18, 19, & 24, with brass cap mkd.

T27S	
R2E	R3E
S 13	S 18
S 24	S 19
1928	

from which

- A fir, 9" dia., bears N.26°E., 75 lks., mkd: T27S R3E S18 BT.
- A fir, 40" dia., bears S.19°E., 88 lks., mkd: T27S R3E S19 BT.
- A fir, 22" dia., bears S.75°W., 137 lks., mkd: T27S R2E S24 BT.
- A fir, 16" dia., bears N.39°W., 63 lks., mkd: T27S R2E S13 BT.