

TOWNSHIP 27 RANGE 03E POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 18; 12, & 13; T27-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 23 Page(s) 9950)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 7, 12, 13, & 18, with brass cap mkd

| | |
|------|------|
| T27S | |
| R2E | R3E |
| S 12 | S 7 |
| S 13 | S 18 |
| 1928 | |

from which

- A cedar, 24" dia., bears N.56°E., 59 lks., mkd: T27S R3E S7 BT.
- A fir, 32" dia., bears S.32°E., 51 lks., mkd: T27S R3E S18 BT.
- A pine, 42" dia., bears S.37°W., 107 lks., mkd: T27S R2E S13 BT.
- A pine, 12" dia., bears N.6°W., 221 lks., mkd: T27S R2E S12 BT.