

TOWNSHIP 27 RANGE 03E POINT IDENTIFIER # 173100

PRIMARY CORNER DESCRIPTION Closing cor. Secs. 5 & 6, only; T28-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed Aug 1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10473)

-----  
Point of intersection of the line bet. secs. 5 & 5, determined as hereinafter described.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for closing cor. of secs. 5 & 6, with brass cap mkd:

T27S R3E  
S 31  
-----  
S 6 | S 5  
T28S R3E  
C C  
1929

from which

A fir, 36" dia., bears S.23°E., 46 lks., mkd: C C T28S R3E S5 BT.

A fir, 9" dia., bears S.70°W., 18 lks., mkd: C C T28S R3E S6 BT.