

TOWNSHIP 27 RANGE 03E POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, W.S.C.E., under special instruction, dated Dec. 27, 1920, surveyed Aug. 1929/Aug 1930 - (DCSO records Vol. 24 Page(s) 10129)

-----  
Set an iron post, 3 ft. long, 2" dia., 18" in the ground, to bedrock, and build a mound of stone, 3 ft. base, 1 ft. high, around the post, for cor. of secs. 5, 6, 7, & 8, with brass cap mkd

T27S R3E  
S 6 | S 5  
S 7 | S 8  
1930

from which

- A pine, 34" dia., bears N.63°E., 60 lks., mkd: T27S R3E S5 BT.
- A fir, 10" dia., bears S.32°E., 60 lks., mkd: T27S R3E S8 BT.
- A cedar, 18" dia., bears S.38°W., 28 lks., mkd: T27S R3E S7 BT.
- A fir, 10" dia., bears N.27°W., 50 lks., mkd: T27S R3E S6 BT.