

TOWNSHIP 27 RANGE 03E POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond, W.S.C.E., under special instruction, dated Dec. 27, 1920, surveyed Aug. 1929/Aug 1930 - (DCSO records Vol. 24 Page(s) 10120)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 20
 S 29
 1929

from which

A fir, 9" dia., bears S.42°E., 15 lks., mkd: 1/4 S29 BT.

A hemlock, 12" dia., bears N.1°W., 35 lks., mkd: 1/4 S20 BT.

Douglas Co. Surveyors Office - Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Bernardino Morales - June 19, 1978 - C.S. File 60/11-18

Found - 1929 U.S. GLO brass cap on a 3/4" I. Rod. Rod is set firmly in ground, but badly bent. Brass cap properly stamped.

Orig. 12" now 20" Hemlock bears N.1°W., 22.8 ft. (Rec. 23.1 ft.) Has a healed scar.

Orig. BT to the SE is gone.

Set - Referencing the location of the rod, I remove, straighten and reset the orig. monument and build a rock mound around pipe. I ADD "T27S R3E" to brass cap.

New BT - A 19" White Fir bears S.29°W., 41.2 ft. scribed "1/4 S29 CS BT" on a double blaze.