

TOWNSHIP 27 RANGE 03E POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Cor Secs 4, 5; 32 & 33 T26-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, W.S.C.E., under special instruction, dated Dec. 27, 1920, surveyed Aug. 1929/Aug 1930 - (DCSO records Vol. 24 Page(s) 10061-2)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 4, 5, 32, & 33, with brass cap mkd

T26S R3E  
S 32|S 33  
S 5|S 4  
T27S  
1930

from which

- A fir, 20" dia., bears N.71°E., 61 lks., mkd: T26S R3E S33 BT.
- A fir, 24" dia., bears S.54½°E., 80 lks., mkd: T27S R3E S4 BT.
- A fir, 34" dia., bears S.68°W., 49 lks., mkd: T27S R3E S5 BT.
- A fir, 24" dia., bears N.12°W., 27 lks., mkd: T26S R3E S32 BT.