

TOWNSHIP 27 RANGE 03E POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, W.S.C.E., under special instruction, dated Dec. 27, 1920, surveyed Aug. 1929/Aug 1930 - (DCSO records Vol. 24 Page(s) 10095)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 15, 16, 21, & 22, with brass cap mkd

T27S R3E  
S 16|S 15  
S 21|S 22  
1929

from which

- A hemlock, 14" dia., bears N.54½°E., 94 lks., mkd: T27S R3E S15 BT.
- A pine, 8" dia., bears S.37½°E., 81 lks., mkd: T27S R3E S22 BT.
- A pine, 36" dia., bears S.49°W., 9 lks., mkd: T27S R3E S21 BT.
- A fir, 16" dia., bears N.30°W., 42 lks., mkd: T27S R3E S16 BT.