

TOWNSHIP 27 RANGE 03E POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, W.S.C.E., under special instruction, dated Dec. 27, 1920, surveyed Aug. 1929/Aug 1930 - (DCSO records Vol. 24 Page(s) 10076)

-----  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 1, 2, 11, & 12, with brass cap mkd

T27S R3E  
S 2 | S 1  
S 11 | S 12  
1929

from which

- A fir, 7" dia., bears N.35°E., 10 lks., mkd: T27S R3E S1 BT.
- A fir, 8" dia., bears S.43°E., 30 lks., mkd: T27S R3E S12 BT.
- A fir, 14" dia., bears S.38°W., 20 lks., mkd: T27S R3E S11 BT.
- A fir, 7" dia., bears N.78°W., 30 lks., mkd: T27S R3E S2 BT.