

TOWNSHIP 27 RANGE 03E POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2; 35 & 36 T26-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, W.S.C.E., under special instruction, dated Dec. 27, 1920, surveyed Aug. 1929/Aug 1930 - (DCSO records Vol. 24 Page(s) 10065)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 1, 2, 35, & 36, with brass cap mkd

T26S R3E  
S 35 | S 36  
S 2 | S 1  
T27S  
1930

from which

- A fir, 12" dia., bears N.59½°E., 74 lks., mkd: T26S R3E S36 BT.
- A fir, 12" dia., bears S.66°E., 47 lks., mkd: T27S R3E S1 BT.
- A fir, 5" dia., bears S.53°W., 39 lks., mkd: T27S R3E S2 BT.
- A pine, 7" dia., bears N.36½°W., 89 lks., mkd: T26S R3E S35 BT.