

TOWNSHIP 27 RANGE 03E POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Township Corner

Alias \_\_\_\_\_ Description (Sec 31 T27-4E = PB 42)  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under special instructions dated Dec. 27, 1920, Surveyed Aug  
1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10484)

-----  
East on the S bdy of sec. 36 at 65.65 chs: Old standard cor.  
of Ts. 27 S, Rs 3 & 4 E., bears N 4.29 chs. Now obliterated.  
(See Flint 1883 survey Vol. 24 Pg. 10051) AT 80 chs:  
Set an iron post, 3 ft. long, 3" dia., 27" in ground, for  
standard cor. of Ts. 27 S., Rs. 3 & 4 E., with brass cap mkd.

S C  
T27S  
R3E|R4E  
S 36|S 31  
T28S R4E  
S 6  
1929

from which

- A fir, 34" dia., bears N.59°E., 23 lks., mkd: S C T27S R4E  
S31 BT.
- A fir, 34" dia., bears N.31°W., 63 lks., mkd: S C T27S R3E  
S36 BT